

Spare-parts catalog

CMS 530 (Type 621)

Component type 002

E10 | E12 | E14 | E16 | E18 | E6.2(12m.10) | E14/12 | E6.2 | E6.2 | E7.2 | E8.2




Table of contents

1	Introduction	9
1.1	Search help	10
1.2	Torques	11
2	Carriage drive	13
2.1	Drive	14
2.1.1	Motor and belt drive	15
2.1.2	Tension bearing	16
2.2	Energy chain and plunger	17
3	Racking	19
3.1	Racking drive	20
4	Needle beds	21
4.1	Needle bed E10	22
4.1.1	Continuation needle bed E10	23
4.2	Needle bed E12	24
4.2.1	Continuation needle bed E12	25
4.3	Needle bed E14	26
4.3.1	Continuation needle bed E14	27
4.4	Needle bed E16	28
4.4.1	Continuation needle bed E16	29
4.5	Needle bed E18	30
4.5.1	Continuation needle bed E18	31
4.6	Needle bed E6.2 (12m.10)	32
4.6.1	Continuation needle bed E6.2(12m.10)	33
4.7	Needle bed E14/12	34
4.7.1	Continuation needle bed E14/12	35
4.8	Needle bed E6.2	36
4.8.1	Continuation needle bed E6.2	37
4.9	Needle bed E7.2	38
4.9.1	Continuation needle bed E7.2	39
4.10	Needle bed E8.2	40
4.10.1	Continuation needle bed E8.2	41
4.11	Needle beds, fixing elements	42
4.12	Cover	43
4.13	Left clamping and cutting bed E10 E12 E14 E6.2 E7.2 E6.2(E12m.10) E14/12	44
4.14	Left clamping and cutting bed E16 E18 E8.2	45
4.15	Right clamping and cutting bed E10 E12 E14 E6.2 E7.2 E6.2(E12m.10) E14/12	46
4.16	Right clamping and cutting bed E16 E18 E8.2	47

5	Carriage	49
5.1	Overview of carriage	50
5.2	Carriage assembly	51
5.3	Carriage cover	52
5.4	Carriage guide	53
5.5	Spare parts package carriage guide rail	54
5.6	Brush holder	55
5.7	Yarn carrier driving without guide part	56
5.8	Yarn carrier driving with guide part	57
5.9	Holding-down jack control	58
5.10	Needle detector	59
5.11	Cam box E10	60
5.11.1	Cams E10	61
5.12	Cam box E12	62
5.12.1	Cams E12	63
5.13	Cam box E14 E14/12	64
5.13.1	Cams E14 E14/12	65
5.14	Cam box E16 E18	66
5.14.1	Cams E14 E14/12	67
5.15	Cam box E6.2	68
5.15.1	Cams E6.2	69
5.16	Cam box E7.2	70
5.16.1	Cams E7.2	71
5.17	Cam box E8.2	72
5.17.1	Cams E8.2	73
5.18	Cam box E12m.10	74
5.18.1	Cams E12m.10	75
6	Main take-down	77
6.1	Main take-down	78
6.1.1	Main take-down on the left	79
6.1.1.1	Swivel-mounted bearing	80
6.1.2	Main take-down on the right	81
6.1.2.1	Mounting plate	82
6.1.2.2	Full floating axle	83
6.1.3	Main take-down in the middle	84
6.1.3.1	Stripper angle	85
6.1.3.2	Rear take-down roller	86
6.1.3.3	Front take-down roller	87
6.1.3.3.1	Front roller elements	88
6.1.3.3.2	Pressure angle rail	89
7	Auxiliary take-down	91

7.1	Auxiliary take-down pre-assembled	92
7.1.1	Right bearing of the auxiliary take-down	93
7.1.2	Left bearing of the auxiliary take-down	94
7.1.3	Metal angle on the left and right complete	95
7.2	Auxiliary take-down in the middle	96
7.3	Motor	97
7.4	Yarn brake at clamping and cutting bed	98
8	Comb take-down	99
8.1	Comb take-down	100
8.2	Comb take-down on the left	101
8.3	Comb take-down on the right	102
8.3.1	Drive shaft of comb	103
8.3.2	Swivel lever comb take-down	104
8.4	Comb take-down in the middle	105
8.4.1	Comb unit	106
8.4.2	Switching lever comb take-down	107
9	Yarn delivery device	109
9.1	Yarn guide system from 14 up to 16 FKE	110
9.2	Yarn guide system with 18 and 20 FKE	111
9.3	Yarn control device	112
9.4	Left yarn guide E10 E12 E14 E6.2(12m.10) E14/12 E7.2	113
9.4.1	Yarn tensioner on the left E10 E12 E14 E16 E18 E14/12 E6.2(12m.10) E7.2 E8.2	114
9.4.1.1	Tension axle on the left E10 E12 E14 E16 E18 E14/12 E6.2(12m.10) E7.2 E8.2	115
9.4.2	Yarn deflector	116
9.4.3	Stopping device on the left	117
9.5	Yarn guide on the left E16 E18 E8.2	118
9.5.1	Yarn brake and yarn deflector	119
9.6	Left yarn guide E6.2	120
9.6.1	Left yarn tensioner E6.2	121
9.6.1.1	Left tension axle E6.2	122
9.7	Right yarn guide E10 E12 E14 E6.2(12m.10) E7.2	123
9.7.1	Yarn tensioner on the right E10 E12 E14 E16 E18 E14/12 E6.2(12m.10) E7.2 E8.2	124
9.7.1.1	Tension axle on the right E10 E12 E14 E16 E18 E14/12 E6.2(12m.10) E7.2 E8.2 ...	125
9.7.2	Stopping device on the right	126
9.8	Right yarn guide E16 E18 E8.2	127
9.9	Right yarn guide E6.2	128
9.9.1	Right yarn tensioners E6.2	129
9.9.1.1	Right tension axle E6.2	130
9.10	Bobbin board	131
9.11	Bar unit	132
9.12	Yarn guide complete	133

9.13	Left friction feed wheel	134
9.14	Right friction feed wheel	135
10	Fluff absorption	137
10.1	Fluff absorption	138
10.1.1	Lint container	139
10.1.2	Set of hose	140
10.1.3	Suction tube	141
11	Operation and control	143
11.1	Input unit	144
11.2	Starting device	145
11.2.1	Bearing of the engaging rod	146
11.3	Collecting area - control	147
11.4	Signal light	148
11.5	Shock stop motion E10 E12 E14 E6.2 E7.2 E6.2(12m.10) E14/12	149
11.6	Shock stop motion E16 E18 E8.2	150
11.7	Measuring device	151
12	Protective units	153
12.1	Lateral safety doors	154
12.2	Panelling	155
12.3	Rear panel	156
13	Electrical equipment	157
13.1	Fuses	158
13.2	Circuit diagram (222) as PDF	159
13.3	Trailing cable	160
13.4	Cable set installation	161
13.4.1	Cable set base 1	162
13.4.2	Loom of cables base 2	163
13.4.3	Loom of cables comb	164
13.4.4	Loom of cables 5XX	165
14	Control electronics	167
14.1	Control cabinet	168
15	Deliverable accessories	169
15.1	Tool	170
15.2	Lubricating stuff	171
15.3	Mechanical parts	172
16	Special attachments	173
16.1	Yarn carrier type 2, E10 12 E14 E7.2 E8.2 E9.2	174

16.2	Yarn carrier type 2, E16 E18	175
16.3	Complete intarsia yarn carriers type 2	176
16.4	Plating yarn carrier 3+6	177
16.5	Plating yarn carrier 4+5	178
16.6	Carriage of plating yarn carrier EW43 EW46	179
16.7	Carriage of plating yarn carrier (adjustable)	180
16.8	Yarn length measuring device on the left complete	181
16.8.1	Yarn length measuring device	182
16.9	Yarn length measuring device on the right complete	183
16.9.1	Yarn length measuring device on the right	184
16.10	Storage feed wheel MSF 2	185
16.11	Bobbin holder on the left	186
16.12	Bobbin holder on the right	187
16.13	Additional bobbin board	188
16.14	Sanding Paper Brake	189
17	Conversion kit with 24 and 32 IFF Type 2	191
17.1	Overview of conversion kit with 24 IFF E10 E12 E14 E16 E18 E8.2	192
17.2	Overview of conversion kit with 24 IFF E6.2	194
17.3	Overview of conversion kit with 24 IFF E7.2 E6.2(12m.10) E14/12	195
17.4	Overview of conversion kit with 32 IFF E10 E12 E14 E16 E18 E8.2	196
17.5	Overview of conversion kit with 32 IFF E6.2	198
17.6	Overview of conversion kit with 32 IFF E7.2 E6.2(12m.10) E14/12	199
17.7	Magnet holder	200
17.8	Additional bobbin board	201
17.9	Parts for the safety door on the left E10 E12 E14 E16 E18 E7.2 E8.2 E6.2(12m.10) E14/12	202
17.9.1	Yarn tensioner on the left E10 E12 E14 E16 E18 E7.2 E8.2 E6.2(12m.10) E14/12	203
17.9.1.1	Tension axle E10 E12 E14 E16 E18 E7.2 E8.2 E6.2(12m.10) E14/12	204
17.9.2	Deflector on the left and on the right	205
17.10	Parts for the right safety door E10 E12 E14 E16 E18 E7.2 E8.2 E6.2(12m.10) E14/12	206
17.10.1	Yarn tensioner on the right E10 E12 E14 E16 E18 E7.2 E8.2 E6.2(12m.10) E14/12	207
17.11	Parts for the safety door on the left E6.2	208
17.11.1	Yarn tensioner on the left E6.2	209
17.11.1.1	Tension axle E6.2	210
17.11.2	Yarn brake	211
17.12	Parts for the right safety door E6.2	212
17.12.1	Yarn tensioner on the right E6.2	213
17.13	Parts for the yarn guide system with 18 FKE	214
17.14	Parts for the yarn guide system with 12 and 14 FKE	215

17.15 Friction feed wheel on the left and on the right complete	216
17.15.1 Friction feed wheel on the left	217
17.15.2 Friction feed wheel on the right	218
17.16 Left clamping and cutting bed E10 E12 E14 E6.2 E7.2 E6.2(E12m.10) E14/12	219
17.17 Left clamping and cutting bed E16 E18 E8.2	220
17.18 Right clamping and cutting bed E10 E12 E14 E6.2 E7.2 E6.2(E12m.10) E14/12	221
17.19 Right clamping and cutting bed E16 E18 E8.2	222
17.20 Stopping device	223
17.21 Yarn guide complete (24 IFF) E10 E12 E14 E7.2 E6.2(12m.10) E14/12	224
17.22 Yarn guide complete (24 IFF) E16 E18 E8.2	225
17.23 Yarn guide complete (24 IFF) E6.2	226
17.24 Yarn guide complete (32 IFF) E10 E12 E14 E7.2 E6.2(12m.10) E14/12	227
17.25 Yarn guide complete (32 IFF) E16 E18 E8.2	228
17.26 Yarn guide complete (32 IFF) E6.2	229

1 Introduction

Imprint

All rights reserved.

The utilisation of texts and pictures, also in extracts, without our agreement is unfavourable to the copyright.

Our products are being developed further continuously. They are therefore subject to technical modifications.

The indications of this catalog are without liability.

©

H. Stoll GmbH & Co.KG

Stollweg 1

D-72760 Reutlingen, Germany

Phone: +49 (07121) 313-289

Fax: +49 (07121) 313-347

e-mail : spareparts@stoll.com

Notes for the order

This catalog serves to order spare parts.

It can only be applied to the machine type recorded on the title page.

When ordering spare parts we imperatively ask for the following indications as otherwise a delivery of spare parts is not possible:

1. Type of machine, gauge, no. of machine.
2. Page no., designation, ID, quantity.

Only genuine STOLL spare parts may be used for repairs.

1.1 Search help

In order to make the search of the spare parts easier, the following elements will be used in the spare parts catalog:

Symbol	Meaning
Σ	Indicates an assembly
	Position indicator with the position number (X).
	Indicates an element of another assembly.
	Indicates an assembly which is represented more detailed beside.
	Indicates an assembly which is represented on another page more detailed.
	Screw torques (z) deviating from the preferential row.
	Detail, represented enlarged in the direction of the arrow.
	Explosion representation, single elements enlarged.
	Indicates a group of parts.
	Indicates the left-hand side or view.
	Indicates the right-hand side or view.
	Indicates a section or a view in the viewing direction.

1.2 Torques

Drehmomente Torques Couples Coppias Momentos de rotación		Festigkeitsklassen Property class Classes de résistance Classi di resistenza Clasas de resistencia		
[Nm] ± 10 % (für $\mu_{\text{ges}} = 0,12$)		4,8	8,8	12,9
Regelgewinde Coarse-pitch thread Filetage à pas gros Filatto regolatore Filete regulador	M3	0,6	1,2	2,5
	M4	1,2	2,5	5
	M5	2,5	5	9
	M6	5	9	18
	M8		18	40
	M10		40	
	M12		80	

Preferential row of screw torques

- Torques are **valid for**:
Connection steel-steel, black, phosphatized, galvanized, rolled or cut thread as well as only for plain (head) supports.
- Torques are valid for:
protected screws with: lock washers, rib heads, coated and clamping screws and nuts. They are also not used for self-grooving threads.
- Torques differing from this preferential row of torques must be taken from the corresponding location in the drawings.


Notes:

2 Carriage drive




2.1 Drive

Pos	Designation	Id		Pos	Designation	Id
Σ	Drive unit			17	Parabolic spring	200 661
11	Drive unit complete	253 877		23	Fan complete	253 692
12	Tension bearing complete	251 581		523	Cap screw M8x12	023 138
14	Toothed belt50AT10/4670	253 890		905	NutM10x12	023 471
16	Spacer pipe	222 099		907	Cap screw M10x25	020 157



2.1.1 Motor and belt drive


Pos	Designation	Id		Pos	Designation	Id
Σ	Drive unit complete	253 877				
1	Drive unit	258 188				
2	Drive bearing complete	255 005				
	2a Drive bearing	241 654		521	Locking ring68x2.5	022 914
	2b Toothed belt pulley	240 616		522	Grooved ball bearing6207-2RS	022 915
	2c Pinion57 AT10 18	242 039		523	Tension set 30X55	023 208
	2d Support of buffer	222 100		524	Cap screw M8X25 12.9	020 142
	520 Cap screw M8X35	020 144		3	Toothed belt	252 594
				500	Pan-head screw M10X25	023 684
				501	Disk10,5X25X2,5	022 178



2.1 Drive


2.1.2 Tension bearing

Pos	Designation		ID		Pos	Designation		ID
Σ	Tension bearing complete		251 581		2	500	Grooved ball bearing625-6305-2RS	255 686
1	Tension bearing		251 560			504	Locking ring 471-25x1,2	251 617
2	Tension roller complete		256 640		501	Cap screw M10x25		023 751
	2a	Tension roller	255 684		502	Washer		020 874
	2b	Axle	251 579		510*	Eccentric		255 499



2.2 Energy chain and plunger

Pos	Designation		ID		Pos	Designation		ID
1	Energy chain 30 links		259 234		5	Continuation carriage driver complete		
4	Threaded spacer		214 584		55	Cable holder	204 688	
501	Cap screw M6x8		023 411		56	Cellular caoutchouc black	202 597	
503	Cap screw M6x16		020 135		57	Cover strip	258 379	
5	Carriage driver complete		258 392		554	Cap screw M6x12	020 134	
	51	Carriage driver	258 380		557	Cap screw M8x30	020 143	
	52	Switch flag carriage driver	258 381		559	Fixing element	026 489	
	52	Cable driver carriage driver	258 378		560	Cap screw M6x8	023 411	
	54	Clamping plate	252 592					



2.2 Energy chain and plunger

Notes:


3 Racking



3.1 Racking drive

3.1 Racking drive

Pos	Designation	Id	Pos	Designation	Id
Σ	Racking				
1	Three-phase AC servo motor racking complete	258 192	505	Washer8,4X20X3	022 175
2	Bearing	227 605	507	Shim0,03x11x80	023 286
3	Spindle bearing	253 262	508	Shim0,05x11x80	023 287
4	Card racking limit switch	229 396	509	Shim0,03x15x85	023 162
5	Racking cover plate	240 721	510	Shim0,05x15x85	023 163
6	Racking strip on the left	240 696	511	Shim0,1x15x85	023 164
7	Racking strip	240 690	512	Shim0,2x15x85	023 170
8	Guide strip	206 382	518	Shim0,03x15x75	023 395
9	Toothed belt150 S 5M 490	229 281	519	Shim 0,05x15x7	023 396
13	Switch plate	240 722	520	Shim0,1x15x75	023 397
19	Stop screw	221 386	521	Shim0,2x15x75	023 398
501	Cap screw M6x16	023 116	900	Cap screw M6x12	022 795
503	Pan-head screw M6x10	023 183	901	Pan-head screw M6x10	023 183
504	Cap screw M8x25	020 142	902	Cap screw M8x30	020 143




4 Needle beds



4.1 Needle bed E10


4.1 Needle bed E10

Pos	Designation	Id		Pos	Designation	Id
Σ	Needle bed complete at the front + rear E10	253 190		16	Cover rail at the rear	213 981
1	Needle bed at the front + rear E10	253 453		17	Cover rail at the front E10	214 036
2	Holding-down jack bed at the rear E10	240 447		18	Cover rail	213 762
3	Holding-down jack bed at the front E10	240 430		19	Cover rail	213 763
41	Needle E10 with round hook	205 398		21	Locating wire D=2,8 1290mm	213 983
42	Coupling part E10-12	253 382		22	Support	241 339
60	Intermediate slider with brake E10-12	255 535		501	Cap screwM5x10	022 918
71	Selection jack E10-12	200 688		502	Cap screwM6x25	020 137
72	Selector spring E10-12	200 691		504	Cap screwM5x22	023 193
10	Knock-over bit E10	239 756		40*	Disk brush	235 612
11	Holding-down jack (trick wall) E10	239 815		42*	Disk brush	202 600
14	Needle bar on the left	213 998		43*	Adjusting bolt	240 765
15	Needle bar on the right	213 999		540*	Cap screwM5x12	020 032




4.1.1 Continuation needle bed E10

Pos	Designation	Id		Pos	Designation	Id
2	Spring steel wire $\varnothing 0,6$ E10-14	213 990		507	Springy thrust piece	023 177
3	Spring steel wire $\varnothing 2,0$	213 996		509	Shim0,02x18,5x34	023 194
12	Limiter on the left E10-14	205 764		510	Shim0,03x18,5x34	023 195
13	Limiter on the right E10-14	205 765		511	Shim0,05x18,5x34	023 196
21	Locating wire $\varnothing 2,8$	213 983		512	Shim0,1x18,5x34	023 197
503	Cap screw M5x8	023 154		513	Shim0,2x18,5x34	023 253




4.2 Needle bed E12

Pos	Designation	Id		Pos	Designation	Id
Σ	Needle bed complete at the front + rear E12	253 165		20	Cover rail at the front E12	214 037
1	Needle bed at the front and rear E12	253 455		21	Cover rail	213 762
3	Main trick wall E12	252 628		22	Cover rail	213 763
4	Pressure slide E10-14	213 919		27	Support	241 339
71	Needle E12	204 009		28	Bush	206 090
72	Coupling part E10-12	253 382		34	Stop screw	235 244
91	Intermediate slider with brake E10-12	255 535		35	Spring steel wire ø2,0	245 320
101	Selection jack E10-12	200 688		40*	Disk brush	235 612
102	Selector spring E10-12	200 691		41*	Container disk brush	233 012
11	Holding-down jack bed at the rear E12	240 448		42*	Disk brush	202 600
12	Holding-down jack bed at the front E12	240 431		43*	Adjusting bolt	240 765
13	Knock-over bit E12	205 013		540*	Cap screw M5x12	020 032
14	Holding-down jack (trick wall) E12	227 821		503	Cap screw M6x14	022 658
17	Needle bar on the left	213 998		506	Cap screw M5x8	023 379
18	Needle bar on the right	213 999		507	Cap screw M5x22	023 193
19	Cover rail at the rear	213 981		509	Setscrew M3,5x3-1	020 512



4.2.1 Continuation needle bed E12


Pos	Designation	Id		Pos	Designation	Id
2	Locating wireø3,4	213 995		508	Cap screw M5x12	022 943
5	Spring steel wire ø 0,6	213 990		513	Springy thrust piece	023 177
15	Limiter on the left E10-E14	205 764		515	Shim0,02x18,5x34	023 194
16	Limiter on the right E10-E14	205 765		516	Shim0,03x18,5x34	023 195
26	Locating wireø 2,8	213 983		517	Shim0,05x18,5x34	023 196
35	Spring steel wire ø2,0	245 320		518	Shim0,1x18,5x34	023 197
505	Cap screw M5x8	023 154		519	Shim0,2X18,5X34	023 253
507	Cap screw M5x22	023 193				



4.3 Needle bed E14


4.3 Needle bed E14

Pos	Designation	Id		Pos	Designation	Id
Σ	Needle bed complete at the front + rear E14	254 218				
1	Needle bed at the front and rear E14	253 456		21	Cover rail	213 762
3	Main trick wall E14	252 629		22	Cover rail	213 763
4	Pressure slide E10-14	213 919		27	Support	241 339
71	Needle E14	209 614		28	Bush	206 090
72	Coupling part E14	253 383		34	Stop screw	235 244
91	Intermediate slider with brake E14	255 536		35	Spring steel wire ø2,0	245 320
10	Selection jack with spring E14	224 725		40*	Disk brush	235 612
11	Holding-down jack bed at the rear E14	240 449		41*	Container disk brush	233 012
12	Holding-down jack bed at the front E14	240 432		42*	Disk brush	202 600
13	Knock-over bit E14	209 649		43*	Adjusting bolt	240 765
14	Holding-down jack trick wall E14	235 262		540*	Cap screw M5x12	020 032
17	Needle bar on the left	213 998		503	Cap screw M6x14	022 658
18	Needle bar on the right	213 999		506	Cap screw M5x8	023 379
19	Cover rail at the rear	213 981		507	Cap screw M5x22	023 193
20	Cover rail at the front E14	214 038		509	SetscrewM3,5x3	020 512



4.3.1 Continuation needle bed E14


Pos	Designation	Id		Pos	Designation	Id
2	Locating wireø3,4	213 995		508	Cap screw M5x12	022 943
5	Spring steel wire ø0,6	213 990		513	Springy thrust piece	023 177
15	Limiter on the left E10-14	205 764		515	Shim0,02x18,5x34	023 194
16	Limiter on the right E10-14	205 765		516	Shim0,03x18,5x34	023 195
26	Locating wireø2,8	213 983		517	Shim0,05x18,5x34	023 196
35	Spring steel wire ø2,0	245 320		518	Shim0,1x18,5x34	023 197
505	Cap screw M5x8	023 154		519	Shim0,2X18,5X34	023 253
507	Cap screw M5x22	023 193				



4.4 Needle bed E16


4.4 Needle bed E16

Pos	Designation	Id	Pos	Designation	Id
Σ	Needle bed complete at the front + rearE16	253 191			
1	Needle bed at the front + rearE16	253 458	21	Cover rail	213 762
3	Main trick wall E16	245 319	22	Cover rail	213 763
4	Pressure strip at the front E5-14	219 536	27	Support	241 339
71	Needle E16	232 243	28	Bush	206 090
72	Coupling part E16-20	253 384	34	Stop screw	235 244
8	Pressure strip at the rear E5-14	219 537	35	Spring steel wire D=2,0 1287 mm	245 320
9	Intermediate slider with brake E16-18	255 537	36	Pressure strip at the rear on the right E16 – E20	223 042
10	Selection jack E16 with selector spring	222 265	40*	Disk brush	235 612
11	Holding-down jack bed at the rear E16	240 450	41*	Container disk brush	233 012
12	Holding-down jack bed at the front E16	240 433	42*	Disk brush	202 600
13	Knock-over bit E16	258 400	43*	Adjusting bolt	240 765
14	Holding-down jack E16	222 504	540*	Cap screwM5x12	020 032
17	Needle bar on the left	213 998	503	Cap screwM6x14	022 658
18	Needle bar on the right	213 999	506	Cap screwM4-M5x8	023 379
19	Cover rail at the rear	213 981	507	Cap screwM5x22	023 193
20	Cover rail at the front E16	222 531	509	Setscrew M3,5x3-1	020 512



4.4.1 Continuation needle bed E16


Pos	Designation	Id		Pos	Designation	Id
2	Locating wire $\varnothing 3,4$	213 995		508	Cap screw M5x12-8.8	022 943
5	Spring steel wire $\varnothing 0,5$	220 759		513	Springy thrust piece	023 177
15	Limiter on the left E16-20	220 821		515	Shim 0,02x18,5x345	023 194
16	Limiter on the right E16-20	220 822		516	Shim 0,03x18,5x34	023 195
26	Locating wire $\varnothing 2,8$	223 922		517	Shim 0,05x18,5x34	023 196
35	Spring steel wire $\varnothing 2,0$	245 320		518	Shim 0,1x18,5x34	023 197
507	Cap screw M5x22	023 193		519	Shim 0,2X18,5X34	023 253



4.5 Needle bed E18


4.5 Needle bed E18

Pos	Designation	Id		Pos	Designation	Id
Σ	Needle bed complete at the front + rear E18	253 192				
1	Needle bed at the front + rear E18	253 459		21	Cover rail	213 762
3	Main trick wall E18	251 051		22	Cover rail	213 763
4	Pressure strip at the front E5-14	219 536		27	Support	241 339
71	Needle E18	239 527		28	Bush	206 090
72	Coupling part E16-20	253 384		34	Stop screw	235 244
8	Pressure strip at the rear E5-14	219 537		35	Spring steel wire D=2,0 1287 mm	245 320
9	Intermediate slider with brake E16-18	255 537		36	Pressure strip at the rear on the right E16 – E20	223 042
10	Selection jack E16-20	222 265		40*	Disk brush	235 612
11	Holding-down jack bed at the rear E18	240 451		41*	Container disk brush	233 012
12	Holding-down jack bed at the front E18	240 434		42*	Disk brush	202 600
13	Knock-over bit 0,8 mm	258 595		43*	Adjusting bolt	240 765
14	Holding-down jack E18	220 770		540*	Cap screw M5x12	020 032
17	Needle bar on the left	213 998		503	Cap screw M6x14	022 658
18	Needle bar on the right	213 999		506	Cap screw M5x8	023 379
19	Cover rail at the rear	213 981		507	Cap screw M5x22	023 193
20	Cover rail at the front E18	220 745		509	SetscrewM3,5x3-1	020 512



4.5.1 Continuation needle bed E18


Pos	Designation	Id		Pos	Designation	Id
2	Locating wire $\varnothing 3,4$	213 995		508	Cap screw M5x12-8.8	022 943
5	Spring steel wire $\varnothing 0,5$	220 759		513	Springy thrust piece	023 177
15	Limiter on the left E16-20	220 821		515	Shim 0,02x18,5x345	023 194
16	Limiter on the right E16-20	220 822		516	Shim 0,03x18,5x34	023 195
26	Locating wire $\varnothing 2,8$	223 922		517	Shim 0,05x18,5x34	023 196
35	Spring steel wire $\varnothing 2,0$	245 320		518	Shim 0,1x18,5x34	023 197
507	Cap screw M5x22	023 193		519	Shim 0,2x18,5x34	023 253



4.6 Needle bed E6.2 (12m.10)


4.6 Needle bed E6.2 (12m.10)

Pos	Designation	Id		Pos	Designation	Id
Σ	Needle bed complete at the front + rearE6.2(12m.10)	255 111		20	Cover rail at the front E12	214 037
1	Needle bed at the front + rear E12	253 455		21	Cover rail	213 762
3	Main trick wall E12	252 628		22	Cover rail	213 763
4	Pressure slide E10-14	213 919		27	Support	241 339
71	Needle E10 with round hook	205 398		28	Bush	206 090
72	Coupling part E10-12	253 382		34	Stop screw	235 244
91	Intermediate slider with brake E10-12	255 535		35	Spring steel wire ø2,0	245 320
101	Selection jack E10-12	200 688		40*	Disk brush	235 612
102	Selector spring E10-12	200 691		41*	Container disk brush	233 012
11	Holding-down jack bed at the rear E12	240 448		42*	Disk brush	202 600
12	Holding-down jack bed at the front E12	240 431		43*	Adjusting bolt	240 765
13	Knock-over bit E12	205 013		540*	Cap screw M5x12	020 032
14	Holding-down jack trick wall E12	227 821		503	Cap screw M6x14	022 658
17	Needle bar on the left	213 998		506	Cap screw M5x8	023 379
18	Needle bar on the right	213 999		507	Cap screw M5x22	023 193
19	Cover rail at the rear	213 981		509	SetscrewM3,5x3	020 512



4.6.1 Continuation needle bed E6.2(12m.10)


Pos	Designation	Id		Pos	Designation	Id
2	Locating wireø3,4	213 995		508	Cap screw M5x12	022 943
5	Spring steel wire ø 0,6	213 990		513	Springy thrust piece	023 177
15	Limiter on the left E10-14	205 764		515	Shim0,02x18,5x34	023 194
16	Limiter on the right E10-14	205 765		516	Shim0,03x18,5x34	023 195
26	Locating wireø 2,8	213 983		517	Shim0,05x18,5x34	023 196
35	Spring steel wire ø2,0	245 320		518	Shim0,1x18,5x34	023 197
505	Cap screw M5x8	023 154		519	Shim0,2X18,5X34	023 253
507	Cap screw M5x22	023 193				



4.7 Needle bed E14/12


4.7 Needle bed E14/12

Pos	Designation	ID	Pos	Designation	ID
Σ	Needle bed complete at the front + rear E14/12	255 102			
1	Needle bed at the front and rear E14	253 456	21	Cover rail	213 762
3	Main trick wall E14	252 629	22	Cover rail	213 763
4	Pressure slide E10-14	213 919	27	Support	241 339
71	NeedleE14/12	227 756	28	Bush	206 090
72	Coupling part E14	253 383	34	Stop screw	235 244
91	Intermediate slider with brake E14	255 536	35	Spring steel wire ø2,0	245 320
10	Selection jack with spring E14	224 725	40*	Disk brush	235 612
11	Holding-down jack bed at the rear E14	240 449	41*	Container disk brush	233 012
12	Holding-down jack bed at the front E14	240 432	42*	Disk brush	202 600
13	Knock-over bit E14	209 649	43*	Adjusting bolt	240 765
14	Holding-down jack (trick wall) E14	235 262	540*	Cap screw M5x12	020 032
17	Needle bar on the left	213 998	503	Cap screw M6x14	022 658
18	Needle bar on the right	213 999	506	Cap screw M5x8	023379
19	Cover rail at the rear	213 981	507	Cap screw M5x22	023 193
20	Cover rail at the front E14	214 038	509	SetscrewM3,5x3	020 512




4.7.1 Continuation needle bed E14/12

Pos	Designation	ID		Pos	Designation	ID
2	Locating wireø3,4	213 995		508	Cap screw M5x12	022 943
5	Spring steel wire ø0,6	213 990		513	Springy thrust piece	023 177
15	Limiter on the left E10-14	205 764		515	Shim0,02x18,5x34	023 194
16	Limiter on the right E10-14	205 765		516	Shim0,03x18,5x34	023 195
26	Locating wireø2,8	213 983		517	Shim0,05x18,5x34	023 196
35	Spring steel wire ø1,95	245 320		518	Shim0,1x18,5x34	023 197
505	Cap screw M5x8	023 154		519	Shim0,2X18,5X34	023 253
507	Cap screw M5x22	023 193				




4.8 Needle bed E6.2

Pos	Designation	Id		Pos	Designation	Id
Σ	Needle bed complete at the front + rear E6.2	255 767		20	Cover rail at the front E12	214 037
1	Needle bed at the front and rear E12	253 455		21	Cover rail	213 762
3	Main trick wall E12	252 628		22	Cover rail	213 763
4	Pressure slide E10-14	213 919		27	Support	241 339
71	Needle E6.2	207 349		28	Bush	206 090
72	Coupling part E10-12	253 382		34	Stop screw	235 244
91	Intermediate slider with brake E10-12	255 535		35	Spring steel wire ø2,0	245 320
101	Selection jack E10-12	200 688		40*	Disk brush	235 612
102	Selector spring E10-12	200 691		41*	Container disk brush	233 012
11	Holding-down jack bed at the rear E6.2	240 455		42*	Disk brush	202 600
12	Holding-down jack bed at the front E6.2	240 438		43*	Adjusting bolt	240 765
13	Knock-over bit E12	205 013		540*	Cap screw M5x12	020 032
14	Holding-down jack (trick wall) E12	227 821		503	Cap screw M6x14	022 658
17	Needle bar on the left	213 998		506	Cap screw M5x8	023 379
18	Needle bar on the right	213 999		507	Cap screw M5x22	023 193
19	Cover rail at the rear	213 981		509	SetscrewM3,5x3	020 512




4.8.1 Continuation needle bed E6.2

Pos	Designation	Id		Pos	Designation	Id
2	Locating wireø3,4	213 995		508	Cap screw M5x12	022 943
5	Spring steel wire ø 0,6	213 990		513	Springy thrust piece	023 177
15	Limiter on the left	205 764		515	Shim0,02x18,5x34	023 194
16	Limiter on the right	205 765		516	Shim0,03x18,5x34	023 195
26	Locating wireø 2,8	213 983		517	Shim0,05x18,5x34	023 196
35	Spring steel wire ø2,0	245 320		518	Shim0,1x18,5x34	023 197
505	Cap screw M5x8	023 154		519	Shim0,2X18,5X34	023 253
507	Cap screw M5x22	023 193				




4.9 Needle bed E7.2

Pos	Designation	Id		Pos	Designation	Id
Σ	Needle bed complete at the front + rearE7.2	253 166				
1	Needle bed at the front and rear E14	253 456		21	Cover rail	213 762
3	Main trick wall E14	252 629		22	Cover rail	213 763
4	Pressure slideE10-14	213 919		27	Support	241 339
71	NeedleE7.2	225 230		28	Bush	206 090
72	Coupling partE14	253 383		34	Stop screw	235 244
91	Intermediate slider with brake E14	255 536		35	Spring steel wire ø2,0	245 320
10	Selection jack with spring E14	224 725		40*	Disk brush	235 612
11	Holding-down jack bed at the rear E7.2	240 456		41*	Container disk brush	233 012
12	Holding-down jack bed at the front E7.2	240 439		42*	Disk brush	202 600
13	Knock-over bit E14	256 912		43*	Adjusting bolt	240 765
14	Holding-down jack trick wallE7.2	258 396		540*	Cap screw M5x12	020 032
17	Needle bar on the left	213 998		503	Cap screw M6x14	022 658
18	Needle bar on the right	213 999		506	Cap screw M5x8	023 379
19	Cover rail at the rear	213 981		507	Cap screw M5x22	023 193
20	Cover rail at the frontE14	214 038		509	SetscrewM3,5x3	020 512



4.9.1 Continuation needle bed E7.2


Pos	Designation	Id		Pos	Designation	Id
2	Locating wireø3,4	213 995		508	Cap screw M5x12	022 943
5	Spring steel wire ø0,6	213 990		513	Springy thrust piece	023 177
15	Limiter on the leftE10-14	205 764		515	Shim0,02x18,5x34	023 194
16	Limiter on the rightE10-14	205 765		516	Shim0,03x18,5x34	023 195
26	Locating wireø2,8	213 983		517	Shim0,05x18,5x34	023 196
35	Spring steel wire ø2,0	245 320		518	Shim0,1x18,5x34	023 197
505	Cap screw M5x8	023 154		519	Shim0,2X18,5X34	023 253
507	Cap screw M5x22	023 193				



4.10 Needle bed E8.2


4.10 Needle bed E8.2

Pos	Designation	Id		Pos	Designation	Id
Σ	Needle bed complete at the front + rearE8.2	254 219				
1	Needle bed at the front + rearE16	253 458		21	Cover rail	213 762
3	Main trick wall E16	245 319		22	Cover rail	213 763
4	Pressure strip at the front E5-14	219 536		27	Support	241 339
71	Needle E18/14	240 026		28	Bush	206 090
72	Coupling partE16-20	253 384		34	Stop screw	235 244
8	Pressure strip at the rear E5-14	219 537		35	Spring steel wire D=2,0 1287 mm	245 320
9	Intermediate slider with brake E16-18	255 537		36	Pressure strip at the rear on the right E16-20	223 042
10	Selection jack E16 with selector spring	222 265		40*	Disk brush	235 612
11	Holding-down jack bed at the rear E16	240 450		41*	Container disk brush	233 012
12	Holding-down jack bed at the front E16	240 433		42*	Disk brush	202 600
13	Knock-over bit 0,8 mm E8.2	258 400		43*	Adjusting bolt	240 765
14	Holding-down jackE16	222 504		540*	Cap screw M5x12	020 032
17	Needle bar on the left	213 998		503	Cap screw M6x14	022 658
18	Needle bar on the right	213 999		506	Cap screw M4-M5x8	023 379
19	Cover rail at the rear	213 981		507	Cap screw M5x22	023 193
20	Cover rail at the frontE16	222 531		509	SetscrewM3,5x3-1	020 512




4.10.1 Continuation needle bed E8.2

Pos	Designation	Id		Pos	Designation	Id
2	Locating wire $\varnothing 3,4$	213 995		508	Cap screw M5x12-8.8	022 943
5	Spring steel wire $\varnothing 0,5$	220 759		513	Springy thrust piece	023 177
15	Limiter on the left E16-20	220 821		515	Shim 0,02x18,5x345	023 194
16	Limiter on the right E16-20	220 822		516	Shim 0,03x18,5x34	023 195
26	Locating wire $\varnothing 2,8$	223 922		517	Shim 0,05x18,5x34	023 196
35	Spring steel wire $\varnothing 2,0$	245 320		518	Shim 0,1x18,5x34	023 197
507	Cap screw M5x22	023 193		519	Shim 0,2X18,5X34	023 253




4.11 Needle beds, fixing elements

Pos	Designation	ID		Pos	Designation	ID
Σ	Fixing elements					
500	Cap screw M8x25	020 142		501	Washer	214 040



4.12 Cover


Pos	Designation	Id		Pos	Designation	Id
1	Cover	241 922		500	Pan-head screwM8x10	241 930



4.13 Left clamping and cutting bed E10 | E12 | E14 | E6.2 | E7.2 | E6.2(E12m.10) | E14/12


4.13 Left clamping and cutting bed
E10 | E12 | E14 | E6.2 | E7.2 | E6.2(E12m.10) | E14/12

Pos	Designation		ID		Pos	Designation		ID
S	Left clamping and cutting bed E10-14		253 162		11	Holding strip		253 176
1	Guide plate EPT on the left E5-14		257 194		12	Tuck needle on the left E5-14		255 813
	1a	Guide plate on the left E10-14	257 190		13	Intermediate cam E10-14		244 591
	1b	Cover rail	253 173		14	Coupling part E5-8		253 381
	1c	Cover rail	253 174		15	Intermediate slider with brake E5-8		255 534
	1d	Locating wire	253 172		16	Selection jack E4-8		200 687
	1e	Guide pin	211 351		17	Selector spring E4-8		200 690
	1f	Locating wire	253 171		18	Spring holder		255 724
	1g	Locating wire	215 927		19	Threaded bolt		255 723
	511	Setscrew M5x5	236 061		500	Cap screw M4x10		023 136
2	Cover on the left complete E10-14		251 120		501	Hexagon nut M4		023 046
3	Catch hook on the left E10-18		255 622		502	Washer 4		020 870
4	Slider E10-14		253 089		503	Pan-head screw M3x18		242 728
5	Intermediate cam E10-14		253 090		504	Tension spring 5x0,5x17,4		023 377
6	Blade		243 948		505	Compression spring 07x4,3x12,1		023 521
7	Clamp on the left complete		244 633		507	Springy thrust piece		023 403
8	Intermediate piece		255 719		520*	Cap screw M6x20		244 824



4.14 Left clamping and cutting bed E16 | E18 | E8.2


Pos	Designation		Id		Pos	Designation		Id
Σ	Left clamping and cutting bed E16-18		253 164		11	Holding strip		253 176
1	Guide plate EPT on the left E16-18		257 196		12	Tuck needle on the left E16-18		255 814
	1a	Guide plate on the left E16-18	257 192		13	Intermediate cam		244 741
	1b	Cover rail	253 173		14	Coupling part E10-12		253 382
	1c	Cover rail	253 174		15	Intermediate slider with brake E10-12		255 535
	1d	Locating wire	253 172		16	Selection jack E10-12		200 688
	1e	Guide pin	211 351		17	Selector spring E10-12		200 691
	1f	Locating wire	253 171		18	Spring holder		255 724
	1g	Locating wire	215 927		19	Threaded bolt		255 723
	511	Setscrew M5x5	236 061		500	Cap screwM4x10		023 136
2	Cover on the left complete E16-18		242 835		501	Hexagon nut M4		023 046
3	Catch hook on the left E10-18		255 622		502	Washer4		020 870
4	SliderE16-18		253 095		503	Pan-head screw M3x18		242 728
5	Intermediate cam E16-18		253 096		504	Tension spring 5x0,5x17,4		023 377
6	Blade		243 948		505	Compression spring 07x4,3x12,1		023 521
7	Clamp on the left complete		244 633		507	Springy thrust piece		023 403
8	Intermediate piece		255 719		520*	Cap screwM6x20		244 824



4.15 Right clamping and cutting bed E10|E12|E14|E6.2|E7.2|E6.2(E12m.10)|E14/12


4.15 Right clamping and cutting bed
E10|E12|E14|E6.2|E7.2|E6.2(E12m.10)|E14/12

Pos	Designation		ID		Pos	Designation	ID
S	Clamping and cutting bed on the right E10-14		253 161		11	Holding strip	253 176
1	Guide plate EPT on the right E5-14		257 193		12	Tuck needle on the right E5-14	255 692
	1a	Guide plate on the rightE5-14	257 189		13	Intermediate cam E10-14	244 591
	1b	Cover rail	253 173		14	Coupling part E5-8	253 381
	1c	Cover rail	253 174		15	Intermediate slider with brake E5-8	255 534
	1d	Locating wire	253 172		16	Selection jack E4-8	200 687
	1e	Guide pin	211 351		17	Selector spring E4-8	200 690
	1f	Locating wire	253 171		18	Spring holder	255 724
	1g	Locating wire	215 927		19	Threaded bolt	255 723
	511	Setscrew M5x5	236 061		500	Cap screwM4x10	023 136
2	Cover on the right complete E10-14		251 119		501	Hexagon nut M4	023 046
3	Catch hook on the right complete E10-18		255 620		502	Washer4	020 870
4	SliderE10-14		253 089		503	Pan-head screw M3x18	242 728
5	Intermediate cam E10-14		253 090		504	Tension spring 5x0,5x17,4	023 377
6	Blade		243 948		505	Compression spring 07x4,3x12,1	023 521
7	Clamp on the right complete		244 602		507	Springy thrust piece	023 403
8	Intermediate piece		255 719		520*	Cap screwM6x20	244 824



4.16 Right clamping and cutting bed E16 | E18 | E8.2

Pos	Designation		Id		Pos	Designation		Id
Σ	Clamping and cutting bed on the right E16-18		253 163		11	Holding strip		253 176
1	Guide plate EPT on the right E16-18		257 195		12	Tuck needle on the right E16-18		255 693
	1a	Guide plate on the rightE16-18	257 191		13	Intermediate cam		244 741
	1b	Cover rail	253 173		14	Coupling part E10-12		253 382
	1c	Cover rail	253 174		15	Intermediate slider with brake E10-12		255 535
	1d	Locating wire	253 172		16	Selection jack E10-12		200 688
	1e	Guide pin	211 351		17	Selector spring E10-12		200 691
	1f	Locating wire	253 171		18	Spring holder		255 724
	1g	Locating wire	215 927		19	Threaded bolt		255 723
	511	Setscrew M5x5	236 061		500	Cap screwM4x10		023 136
2	Cover on the right complete E16-18		242 836		501	Hexagon nut M4		023 046
3	Catch hook on the right E10-18		255 620		502	Washer4		020 870
4	SliderE16-18		253 095		503	Pan-head screw M3x18		242 728
5	Intermediate cam E16-18		253 096		504	Tension spring 5x0,5x17,4		023 377
6	Blade		243 948		505	Compression spring 07x4,3x12,1		023 521
7	Clamp on the right complete		244 602		507	Springy thrust piece		023 403
8	Intermediate piece		255 719		520*	Cap screwM6x20		244 824



4.16 Right clamping and cutting bed E16 | E18 | E8.2


Notes:

5 Carriage

5.1 Overview of carriage


5.1 Overview of carriage

Pos	Designation	ID	Pos	Designation	ID
Σ	Carriage 3 cam boxes complete		1	Cam box (set) complete	
	E10	253 254		E10	259 239
	E12	253 188		E12	259 240
	E14 E14/12	255 105		E14 E14/12	259 241
	E16 E18	253 255		E16 E18	259 242
	E6.2(12m.10)	255 113		E6.2 (12m.10)	259 243
	E6.2	255 768		E6.2	259 244
	E7.2	253 150		E7.2	259 245
	E8.2	255 098		E8.2	259 246
2	FF driving outside complete	245 297	9	Wiper (felt)	241 411
3	FF driving in the middle complete	245 298	10	Bolts	212 392
4	Holding-down jack control complete		11	Bolts	243 171
	E10	259 626	12	Cover plate on the left	250 274
	E12 E14 E6.2 E6.2(12m.10) E14/12	259 627	13	Cover plate on the right	250 275
	E16 E18	259 628	14	Motor unit complete(ATM)	251 827
	E7.2	259 629	14a	Gear rack at the top complete	251 817
	E8.2	259 630	14b	Gear rack at the bottom complete	251 818
5	Carriage assembly 3 cam boxes complete	253 152	17	Guide plate at the rear on the left	245 323
6*	Sinker opener complete	256 623	18	Guide plate at the rear on the right	245 324
7	Distributor	254 914	501	Cap screw M4x35	023 550
8	Selection system complete		526	Cap screw M4x20	023 171
	E10 E12 E6.2 6.2(12m.10)	216 219			
	E14 E14/12 E7.2	229 300			
	E16 E18 E8.2	220 114			




5.2 Carriage assembly

Pos	Designation	ID		Pos	Designation	ID
Σ	Carriage assembly 3 cam boxes complete	253 152		13	Locating bolt linking spot	244 179
1	Carriage frame, 3 cam boxes	258 008		500	Cap screwM8x30	020 143
2	Carriage part, 3 cam boxes	254 499		502	Pan-head screwM6x10	023 183
4	Shim	225 312		504	Circlip6	021 022
5	Shoulder screw	211 750		514	Dowel pin 5x14	020 670
8	Bush	207 546		515	Threaded bush M12x11,5	041 863
9	Bush	209 275		522	Shim 0,2x10x70	023 699
10	Bush	209 274		523	Shim 0,1x10x70	023 698
11	Eccentric	222 983		524	Shim 0,05x10x70	023 697




5.3 Carriage cover

Pos	Designation	ID	Pos	Designation	ID
1	Carriage cover at the top 3 cam boxes complete	257 103	10	Locating bolt	242 382
	1a Carriage cover at the top 3 cam boxes 5Z	253 148	500	Hexagon nutM6	257 088
2	Carriage cover at the rear complete 3 cam boxes	259 277	501	Washer6.1x9x0,5	023 554
	2a Carriage cover at the rear 3 cam boxes 5Z	255 417	502	Serrated lock washer 6,4	022 385
3	Carriage cover front 3 cam boxes	259 276	503	O-ring 3x2	242 420
	3a Carriage cover at the front 3 cam boxes 5Z	255 416	504	Compression spring0,48x7,02x17,29	023 654




5.4 Carriage guide

Pos	Designation	ID		Pos	Designation	ID
6	Bearing bolt eccentric 0,5	242 060		510	Shim ring 12x18x1	023 315
7	Bearing bolt eccentric 0,5	240 624		511	Shim ring 10x16x1	023 260
12	Bolt pre-assembled	244 283		518	Grooved ball bearing 62201-2RS	241 408
508	NutM10	023 316		519	Grooved ball bearing 62300-2RS1	242 070




5.5 Spare parts package carriage guide rail

Pos	Designation	ID		Pos	Designation	ID
Σ	Spare parts package carriage guide rail 5XX	243 423		501	Shim 0,05x22x42	243 291
1	Carriage guide rail	239 926		502	Shim 0,10x22x42	243 292
2	Adjusting eccentric	241 219		503	Shim 0,20x22x42	243 293
500	Shim 0,03x22x42	243 289		510*	Cap screw M8x20	020 141



5.6 Brush holder


Pos	Designation	ID		Pos	Designation	ID
Σ	Brush holder complete			4	Brush	
	E10 E12 E14 E14/12 E6.2 E7.2 (E12m.10)	252 749			E10 E12 E14 E14/12 E6.2 E7.2 6.2(E12m.10)	243 074
	E16 E18 E8.2	213 710			E16 E18 E8.2	203 254
				500	Countersunk head screw M4x12	023 062
1	Brush holder	213 009		501	Hexagon nut M8x5	023 750
2	Brush clamp	213 010		502	Shim ring 5x10x0,5	023 348
3	Threaded rod	209 740		503	Locking ring 5x0,6	023 347



5.7 Yarn carrier driving without guide part


5.7 Yarn carrier driving without guide part

Pos	Designation	ID		Pos	Designation	ID
Σ	FF driving outside complete	245 297		6	Switch mechanism	251 137
1	Yarn carrier plunger on the right complete	243 080		500	Cap screwM4x16-I-Torx	258 336
2	Yarn carrier plunger on the left complete	243 118		501	Cap screwM4x25-I-Torx	245 305
3	Holding angle for jack	245 313		502	Cap screwM3x12-12.9	022 648
4	Holding block outside	245 294		900	Shoulder screw	231 899
5	Card yarn carrier final stagesOKC	300 960		901	Cap screwM6x16	020 135




5.8 Yarn carrier driving with guide part

Pos	Designation	ID		Pos	Designation	ID
Σ	YC driving in the middle complete	245 298		7	Card yarn carrier final stagesOKC	300 960
1	Yarn carrier plunger on the right complete	243 080		500	Cap screwM4x16-I-Torx	258 336
2	Yarn carrier plunger on the left complete	243 118		501	Cap screwM4x25-I-Torx	245 305
3	Holding angle for jack	245 313		502	Cap screwM3x12-12.9	022 648
4	Holding block in the middle	245 308		503	Screw KB60x20	243 625
5	Switch mechanism	251 137		900	Shoulder screw	231 899
6	Guide part	239 972		901	Cap screwM6x16	020 135




5.9 Holding-down jack control

Pos	Designation	ID	Pos	Designation	ID
Σ	Holding-down jack control complete		22	E7.2	256 394
	E10	259 626		E8.2	256 395
	E12 E14 E6.2 E6.2(12m.10) E14/12	259 627	23	Slider on the left complete	
	E16 E18	259 628		E10	256 396
	E7.2	259 629		E12 E14 E6.2 E6.2(12m.10) E14/12	256 397
	E8.2	259 630		E16 E18	256 398
1	Assembly plate complete	256 311		E7.2	256 399
4	Adjusting plate	256 388		E8.2	256 400
5	Plunger	256 059	24	Bolts	209 722
11	Slider on the right	259 457	500	Pan-head screw M4x6	023 427
12	Slider on the left	259 456	501	Cap screw M4x12	241 859
21	Base plate	259 170	506	Cap screw M4x8	022 501
22	Slider on the right complete		520	Shim ring 5x8x0.5	256 371
	E10	256 391	521	Locking ring 5x0,6	023 347
	E12 E14 E6.2 E6.2(12m.10) E14/12	256 392	30*	Eccentric of holding-down jack control	256 994
	E16 E18	256 393			



5.10 Needle detector


Pos	Designation	ID	Pos	Designation	ID
Σ	Needle detector				
1	Needle detector pre-assembled E10-18	256 475	504	Compression spring0,4x4x11,2	256 952
11	Cable of needle detector complete	221 207	505	Circlip	021 018
12	Retainer	256 476	506	Circlip	023 565
13	Switch rocker	256 477	507	Cable tape 92x2,4	008 378
14	Set-out plate	256 094	2	Sensor pre-assembled E10 E12 E14 E6.2 E7.2 E6.2(12m.10) E14/12	256 454
15	Bolts	256 492	21	Sensor E10 E12 E14	255 758
16	Stop bolt	256 493	22	Angle	255 757
500	Pan-head screw M5x10	023 247	520	Pan-head screw M4x6	023 427
501	Pan-head screw M2x8	258 310	2	Sensor pre-assembled E16 E18 E8.2	256 784
502	Dowel pin 4x10-A-St	023 753	21	Sensor E16 E18 E8.2	255 759
503	Compression spring4,3x0,45x10	021 398	22	Angle	255 757
			520	Pan-head screw M4x6	023 427



5.11 Cam box E10


5.11 Cam box E10

Pos	Designation		ID		Pos	Designation		ID
Σ	Cam box set complete E10		259 239		37	c	Compression spring	257 082
1	Cam plate E10-18		258 159			d	Circlip	023 565
22	Stay bolt		254 839			E	Washer	020 877
23	Guide of pressure part complete		253 480		38	Slider pressure part complete		251 834
34	Loop sinking cam on the left completeE10		254 246		43	Holding piece		251 828
35	Loop sinking cam on the right completeE10		254 247		44	Limiting cam complete E10-18		251 889
36	Rod guide on the left complete		252 662		505	Shim0,03x12x75		022 828
37	Rod guide on the right complete		252 663		506	Shim0,05x12x75		022 829
	a	Rod guide part	252 660		507	Shim0,1x12x75		022 830
	b	Spring rod	252 661		508	Shim0,2x12x75		022 831



5.11.1 Cams E10


Pos	Designation	Id		Pos	Designation	Id
2	Entry cam on the left at the top E10-18	256 690		24	Tuck pressure part	253 828
3	Entry cam on the right at the top E10-18	256 691		25	Limiting cam E10 E7.2	251 993
4	Entry cam at the top E10-18	256 689		26	Pointer E10	251 994
5	Knitting position cam E10-14 E6.2 E7.2	255 021		27	Screw	210 335
6	Plate on the left E10-18	255 389		28	Stitch cam on the left E10-14 E7.2	254 331
7	Plate on the right E10-18	255 390		29	Stitch cam on the right E10-14 E7.2	254 332
8	Entry cam on the left E10-18	255 391		30	Tuck limiting cam E10 E7.2	254 295
9	Entry cam on the right E10-18	255 392		31	Raising cam plate E10-18	251 992
10	Pressure strip E10-14	255 540		32	Receiving cam E10 E12	251 997
11	Cam guide at the top E10-18	258 161		33	Raising cam without split-stitch E10 E12	254 334
12	Cam guide E10-18	255 541			Raising cam with split-stitch E10 E12	254 335
13	Cam on the left E10-18	255 613		39	Cam at the right E10-18	258 154
14	Cam at the right E10-18	255 614		40	Knitting position cam on the left E10-14 E6.2 E7.2	255 022
15	Limiting cam on the left E10-18	251 886		41	Knitting position cam on the right E10-14 E6.2 E7.2	255 023
16	Limiting cam on the right E10-18	251 887		45	Cam E10-18	251 888
17	Cam on the left E10-18	258 153		49	Limiting cam E10-18	251 885
18	Cam E10-18	258 152		50	Transfer pressure part	253 838
19	Selection cam on the left E10-18	251 876		51	Offering cam	210 185
20	Selection cam on the right E10-18	251 877		500	Cap screw M4x8	020 091
21	Selection cam E10-18	251 875		510	Cap screw M3x8	020 081



5.12 Cam box E12


5.12 Cam box E12

Pos	Designation		ID	Pos	Designation		ID
Σ	Cam box set complete E12		259 240	37	c	Compression spring	257 082
1	Cam plate E10-18		258 159		d	Circlip	023 565
22	Stay bolt		254 839		E	Washer	020 877
23	Guide of pressure part complete		253 480	38	Slider pressure part complete		251 834
34	Loop sinking cam on the left completeE12-14		254 248	43	Holding piece		251 828
35	Loop sinking cam on the right completeE12-14		254 249	44	Limiting cam complete E10 -18		251 889
36	Rod guide on the left complete		252 662	505	Shim0,03x12x75		022 828
37	Rod guide on the right complete		252 663	506	Shim0,05x12x75		022 829
	a	Rod guide part	252 660	507	Shim0,1x12x75		022 830
	b	Spring rod	252 661	508	Shim0,2x12x75		022 831




5.12.1 Cams E12

Pos	Designation	Id		Pos	Designation	Id
2	Entry cam on the left at the top E10-18	256 690		24	Tuck pressure part	253 828
3	Entry cam on the right at the top E10-18	256 691		25	Limiting cam E12-14	252 522
4	Entry cam at the top E10-18	256 689		26	Pointer E10	251 994
5	Knitting position cam E10-14 E6.2 E7.2	255 021		27	Screw	210 335
6	Plate on the left E10-18	255 389		28	Stitch cam on the left E10-14 E7.2	254 331
7	Plate on the right E10-18	255 390		29	Stitch cam on the right E10-14 E7.2	254 332
8	Entry cam on the left E10-18	255 391		30	Tuck limiting cam E12-14	254 298
9	Entry cam on the right E10-18	255 392		31	Raising cam plate E10-18	251 992
10	Pressure strip E10-14	255 540		32	Receiving cam E10 E12	251 997
11	Cam guide at the top E10-18	258 161		33	Raising cam without split-stitch E10 E12	254 334
12	Cam guide E10-18	255 541			Raising cam with split-stitch E10 E12	254 335
13	Cam on the left E10-18	255 613		39	Cam at the right E10-18	258 154
14	Cam at the right E10-18	255 614		40	Knitting position cam on the left E10-14 E6.2 E7.2	255 022
15	Limiting cam on the left E10-18	251 886		41	Knitting position cam on the right E10-14 E6.2 E7.2	255 023
16	Limiting cam on the right E10-18	251 887		45	Cam E10-18	251 888
17	Cam on the left E10-18	258 153		49	Limiting cam E10-18	251 885
18	Cam E10-18	258 152		50	Transfer pressure part	253 838
19	Selection cam on the left E10-18	251 876		51	Offering cam	210 185
20	Selection cam on the right E10-18	251 877		500	Cap screw M4x8	020 091
21	Selection cam E10-18	251 875		510	Cap screw M3x8	020 081




5.13 Cam box E14 | E14/12

Pos	Designation		ID	Pos	Designation		ID
Σ	Cam box set complete E14 E14/12		259 241	37	c	Compression spring	257 082
1	Cam plate E10-E18		258 159		d	Circlip	023 565
22	Stay bolt		254 839		E	Washer	020 877
23	Guide of pressure part complete		253 480	38	Slider pressure part complete		251 834
34	Loop sinking cam on the left completeE12-14		254 248	43	Holding piece		251 828
35	Loop sinking cam on the right completeE12-14		254 249	44	Limiting cam complete E10-18		251 889
36	Rod guide on the left complete		252 662	505	Shim0,03x12x75		022 828
37	Rod guide on the right complete		252 663	506	Shim0,05x12x75		022 829
	a	Rod guide part	252 660	507	Shim0,1x12x75		022 830
	b	Spring rod	252 661	508	Shim0,2x12x75		022 831




5.13.1 Cams E14 | E14/12

Pos	Designation	ID		Pos	Designation	ID
2	Entry cam on the left at the top E10-18	256 690		24	Tuck pressure part	253 828
3	Entry cam on the right at the top E10-18	256 691		25	Limiting cam E12-14	252 522
4	Entry cam at the top E10-18	256 689		26	Pointer E10	251 994
5	Knitting position cam E10-14 E6.2 E7.2	255 021		27	Screw	210 335
6	Plate on the left E10-18	255 389		28	Stitch cam on the left E10-14 E7.2	254 331
7	Plate on the right E10-18	255 390		29	Stitch cam on the right E10-14 E7.2	254 332
8	Entry cam on the left E10-18	255 391		30	Tuck limiting cam E12 E14	254 298
9	Entry cam on the right E10-18	255 392		31	Raising cam plate E10-18	251 992
10	Pressure strip E10-14	255 540		32	Receiving cam E14	252 607
11	Cam guide at the top E10-18	258 161		33	Raising cam without split-stitch E14	254 336
12	Cam guide E10-18	255 541			Raising cam with split-stitch E14	254 337
13	Cam on the left E10-18	255 613		39	Cam at the right E10-18	258 154
14	Cam at the right E10-18	255 614		40	Knitting position cam on the left E10-14 E6.2 E7.2	255 022
15	Limiting cam on the left E10-18	251 886		41	Knitting position cam on the right E10-14 E6.2 E7.2	255 023
16	Limiting cam on the right E10-18	251 887		45	Cam E10-18	251 888
17	Cam on the left E10-18	258 153		49	Limiting cam E10-18	251 885
18	Cam E10-18	258 152		50	Transfer pressure part	253 838
19	Selection cam on the left E10-18	251 876		51	Offering cam	210 185
20	Selection cam on the right E10-18	251 877		500	Cap screw M4x8	020 091
21	Selection cam E10-18	251 875		510	Cap screw M3x8	020 081




5.14 Cam box E16|E18

Pos	Designation	ID	Pos	Designation	ID
Σ	Cam box set complete E16 E18	259 242	37	c Compression spring	257 082
1	Cam plate E10-18	258 159		d Circlip	023 565
22	Stay bolt	254 839		E Washer	020 877
23	Guide of pressure part complete	253 480	38	Slider pressure part complete	251 834
34	Loop sinking cam on the left completeE16-18	251 965	43	Holding piece	251 828
35	Loop sinking cam on the right completeE16-18	251 966	44	Limiting cam complete E10-18	251 889
36	Rod guide on the left complete	252 662	505	Shim0,03x12x75	022 828
37	Rod guide on the right complete	252 663	506	Shim0,05x12x75	022 829
	a Rod guide part	252 660	507	Shim0,1x12x75	022 830
	b Spring rod	252 661	508	Shim0,2x12x75	022 831



5.14.1 Cams E14|E14/12


Pos	Designation	ID		Pos	Designation	ID
2	Entry cam on the left at the top E10-18	256 690		24	Tuck pressure part	253 828
3	Entry cam on the right at the top E10-18	256 691		25	Limiting cam E16-18	252 646
4	Entry cam at the top E10-18	256 689		26	Pointer E16-18	252 656
5	Knitting position cam E16-18 E8.2	255 027		27	Screw	210 335
6	Plate on the left E10-18	255 389		28	Stitch cam on the left E16-18 E8.2	254 338
7	Plate on the right E10-18	255 390		29	Stitch cam on the right E16-18 E8.2	254 339
8	Entry cam on the left E10-18	255 391		30	Tuck limiting cam E16-18	254 299
9	Entry cam on the right E10-18	255 392		31	Raising cam plate E10-18	251 992
10	Pressure strip E16-18	256 681		32	Receiving cam E16-18	252 654
11	Cam guide at the top E10-18	258 161		33	Raising cam without split-stitch E16-18	254 340
12	Cam guide E10-18	255 541			Raising cam with split-stitch E16-18	254 341
13	Cam on the left E10-18	255 613		39	Cam at the right E10-18	258 154
14	Cam at the right E10-18	255 614		40	Knitting position cam on the left E16-18 E8.2	255 028
15	Limiting cam on the left E10-18	251 886		41	Knitting position cam on the right E16-18 E8.2	255 029
16	Limiting cam on the right E10-18	251 887		45	Cam E10-18	251 888
17	Cam on the left E10-18	258 153		49	Limiting cam E10-18	251 885
18	Cam E10-18	258 152		50	Transfer pressure part	253 838
19	Selection cam on the left E10-18	251 876		51	Offering cam	210 185
20	Selection cam on the right E10-18	251 877		500	Cap screw M4x8	020 091
21	Selection cam E10-18	251 875		510	Cap screw M3x8	020 081



5.15 Cam box E6.2


5.15 Cam box E6.2

Pos	Designation		ID	Pos	Designation		ID
Σ	Cam box set complete E6.2		259 244	37	c	Compression spring	257 082
1	Cam plate E10-18		258 159		d	Circlip	023 565
22	Stay bolt		254 839		E	Washer	020 877
23	Guide of pressure part complete		253 480	38	Slider pressure part complete		251 834
34	Loop sinking cam on the left completeE12-14		254 248	43	Holding piece		251 828
35	Loop sinking cam on the right completeE12-14		254 249	44	Limiting cam complete E10-18		251 889
36	Rod guide on the left complete		252 662	505	Shim0,03x12x75		022 828
37	Rod guide on the right complete		252 663	506	Shim0,05x12x75		022 829
	a	Rod guide part	252 660	507	Shim0,1x12x75		022 830
	b	Spring rod	252 661	508	Shim0,2x12x75		022 831



5.15.1 Cams E6.2


Pos	Designation	ID		Pos	Designation	ID
2	Entry cam on the left at the top E10-18	256 690		24	Tuck pressure part	253 828
3	Entry cam on the right at the top E10-18	256 691		25	Limiting cam E6.2	252 955
4	Entry cam at the top E10-18	256 689		26	Pointer E10	251 994
5	Knitting position cam E10-14 E6.2 E7.2	255 021		27	Screw	210 335
6	Plate on the left E10-18	255 389		28	Stitch cam on the left E6.2	254 342
7	Plate on the right E10-18	255 390		29	Stitch cam on the right E6.2	254 343
8	Entry cam on the left E10-18	255 391		30	Tuck limiting cam E6.2	254 301
9	Entry cam on the right E10-18	255 392		31	Raising cam plate E10-18	251 992
10	Pressure strip E10-14	255 540		32	Receiving cam E6.2	252 960
11	Cam guide at the top E10-18	258 161		33	Raising cam without split-stitch E6.2	254 344
12	Cam guide E10-18	255 541			Raising cam with split-stitch E6.2	254 345
13	Cam on the left E10-18	255 613		39	Cam at the right E10-E18	258 154
14	Cam at the right E10-18	255 614		40	Knitting position cam on the left E10-14 E6.2 E7.2	255 022
15	Limiting cam on the left E10-18	251 886		41	Knitting position cam on the right E10-14 E6.2 E7.2	255 023
16	Limiting cam on the right E10-18	251 887		45	Cam E10-18	251 888
17	Cam on the left E10-18	258 153		49	Limiting cam E10-18	251 885
18	Cam E10-18	258 152		50	Transfer pressure part	253 838
19	Selection cam on the left E10-18	251 876		51	Offering cam	210 185
20	Selection cam on the right E10-18	251 877		500	Cap screw M4x8	020 091
21	Selection cam E10-18	251 875		510	Cap screw M3x8	020 081



5.16 Cam box E7.2


5.16 Cam box E7.2

Pos	Designation		ID		Pos	Designation		ID
Σ	Cam box set complete E7.2		259 245		37	c	Compression spring	257 082
1	Cam plate E10-18		258 159			d	Circlip	023 565
22	Stay bolt		254 839			E	Washer	020 877
23	Guide of pressure part complete		253 480		38	Slider pressure part complete		251 834
34	Loop sinking cam on the left completeE12-14		254 248		43	Holding piece		251 828
35	Loop sinking cam on the right completeE12-14		254 249		44	Limiting cam complete E10 -18		251 889
36	Rod guide on the left complete		252 662		505	Shim0,03x12x75		022 828
37	Rod guide on the right complete		252 663		506	Shim0,05x12x75		022 829
	a	Rod guide part	252 660		507	Shim0,1x12x75		022 830
	b	Spring rod	252 661		508	Shim0,2x12x75		022 831



5.16.1 Cams E7.2


Pos	Designation	Id		Pos	Designation	Id
2	Entry cam on the left at the top E10-18	256 690		24	Tuck pressure part	253 828
3	Entry cam on the right at the top E10-18	256 691		25	Limiting cam E10 E7.2	251 993
4	Entry cam at the top E10-18	256 689		26	Pointer E10	251 994
5	Knitting position cam E10-14 E6.2 E7.2	255 021		27	Screw	210 335
6	Plate on the left E10-18	255 389		28	Stitch cam on the left E10-14 E7.2	254 331
7	Plate on the right E10-18	255 390		29	Stitch cam on the right E10-14 E7.2	254 332
8	Entry cam on the left E10-18	255 391		30	Tuck limiting cam E10 E7.2	254 295
9	Entry cam on the right E10-18	255 392		31	Raising cam plate E10-18	251 992
10	Pressure strip E10-14	255 540		32	Receiving cam E10-12	251 997
11	Cam guide E10-18	258 161		33	Raising cam without split-stitch E10-12	254 334
12	Cam guide E10-18	255 541			Raising cam with split-stitch E10-12	254 335
13	Cam on the left E10-18	255 613		39	Cam at the right E10-18	258 154
14	Cam at the right E10-18	255 614		40	Knitting position cam on the left E10-14 E6.2 E7.2	255 022
15	Limiting cam on the left E10-18	251 886		41	Knitting position cam on the right E10-14 E6.2 E7.2	255 023
16	Limiting cam on the right E10-18	251 887		45	Cam E10-18	251 888
17	Cam on the left E10-18	258 153		49	Limiting cam E10-18	251 885
18	Cam E10-18	258 152		50	Transfer pressure part	253 838
19	Selection cam on the left E10-18	251 876		51	Offering cam	210 185
20	Selection cam on the right E10-18	251 877		500	Cap screw M4x8	020 091
21	Selection cam E10-18	251 875		510	Cap screw M3x8	020 081



5.17 Cam box E8.2


5.17 Cam box E8.2

Pos	Designation		ID		Pos	Designation		ID
Σ	Cam box set complete E8.2		259 246		37	c	Compression spring	257 082
1	Cam plate E10-18		258 159			d	Circlip	023 565
22	Stay bolt		254 839			E	Washer	020 877
23	Guide of pressure part complete		253 480		38	Slider pressure part complete		251 834
34	Loop sinking cam on the left completeE16-18		251 965		43	Holding piece		251 828
35	Loop sinking cam on the right completeE16-18		251 966		44	Limiting cam complete E10-18		251 889
36	Rod guide on the left complete		252 662		505	Shim0,03x12x75		022 828
37	Rod guide on the right complete		252 663		506	Shim0,05x12x75		022 829
	a	Rod guide part	252 660		507	Shim0,1x12x75		022 830
	b	Spring rod	252 661		508	Shim0,2x12x75		022 831



5.17.1 Cams E8.2


Pos	Designation	Id		Pos	Designation	Id
2	Entry cam on the left at the top E10-18	256 690		24	Tuck pressure part	253 828
3	Entry cam on the right at the top E10-18	256 691		25	Limiting cam E8.2	252 974
4	Entry cam at the top E10-18	256 689		26	Pointer E16-18	252 656
5	Knitting position cam E16-18 E8.2	255 027		27	Screw	210 335
6	Plate on the left E10-18	255 389		28	Stitch cam on the left E16-18 E8.2	254 338
7	Plate on the right E10-18	255 390		29	Stitch cam on the right E16-18 E8.2	254 339
8	Entry cam on the left E10-18	255 391		30	Tuck limiting cam E8.2	254 302
9	Entry cam on the right E10-18	255 392		31	Raising cam plate E10-18	251 992
10	Pressure strip E16-18	256 681		32	Receiving cam E8.2	252 975
11	Cam guide at the top E10-18	258 161		33	Raising cam without split-stitch E16-18	254 340
12	Cam guide E10-18	255 541			Raising cam with split-stitch E16-18	254 341
13	Cam on the left E10-18	255 613		39	Cam at the right E10-18	258 154
14	Cam at the right E10-18	255 614		40	Knitting position cam on the left E16-18 E8.2	255 028
15	Limiting cam on the left E10-18	251 886		41	Knitting position cam on the right E16-18 E8.2	255 029
16	Limiting cam on the right E10-18	251 887		45	Cam E10-18	251 888
17	Cam on the left E10-18	258 153		49	Limiting cam E10-18	251 885
18	Cam E10-18	258 152		50	Transfer pressure part	253 838
19	Selection cam on the left E10-18	251 876		51	Offering cam	210 185
20	Selection cam on the right E10-18	251 877		500	Cap screw M4x8	020 091
21	Selection cam E10-18	251 875		510	Cap screw M3x8	020 081



5.18 Cam box E12m.10


5.18 Cam box E12m.10

Pos	Designation		ID	Pos	Designation		ID
Σ	Cam box set complete E12m.10		259 243	37	c	Compression spring	257 082
1	Cam plate E10-18		258 159		d	Circlip	023 565
22	Stay bolt		254 839		E	Washer	020 877
23	Guide of pressure part complete		253 480	38	Slider pressure part complete		251 834
34	Loop sinking cam on the left completeE12-14		254 248	43	Holding piece		251 828
35	Loop sinking cam on the right completeE12-14		254 249	44	Limiting cam complete E10 -18		251 889
36	Rod guide on the left complete		252 662	505	Shim0,03x12x75		022 828
37	Rod guide on the right complete		252 663	506	Shim0,05x12x75		022 829
	a	Rod guide part	252 660	507	Shim0,1x12x75		022 830
	b	Spring rod	252 661	508	Shim0,2x12x75		022 831



5.18.1 Cams E12m.10


Pos	Designation	Id		Pos	Designation	Id
2	Entry cam on the left at the top E10-18	256 690		24	Tuck pressure part	253 828
3	Entry cam on the right at the top E10-18	256 691		25	Limiting cam E10 E7.2	251 993
4	Entry cam at the top E10-18	256 689		26	Pointer E10	251 994
5	Knitting position cam E10-14 E6.2 E7.2	255 021		27	Screw	210 335
6	Plate on the left E10-18	255 389		28	Stitch cam on the left E10-14 E7.2	254 331
7	Plate on the right E10-18	255 390		29	Stitch cam on the right E10-14 E7.2	254 332
8	Entry cam on the left E10-18	255 391		30	Tuck limiting cam E10 E7.2	254 295
9	Entry cam on the right E10-18	255 392		31	Raising cam plate E10-18	251 992
10	Pressure strip E10-14	255 540		32	Receiving cam E10-12	251 997
11	Cam guide at the top E10-18	258 161		33	Raising cam without split-stitch E10-12	254 334
12	Cam guide E10-18	255 541			Raising cam with split-stitch E10-12	254 335
13	Cam on the left E10-18	255 613		39	Cam at the right E10-18	258 154
14	Cam at the right E10-18	255 614		40	Knitting position cam on the left E10-14 E6.2 E7.2	255 022
15	Limiting cam on the left E10-18	251 886		41	Knitting position cam on the right E10-14 E6.2 E7.2	255 023
16	Limiting cam on the right E10-18	251 887		45	Cam E10-18	251 888
17	Cam on the left E10-18	258 153		49	Limiting cam E10-18	251 885
18	Cam E10-18	258 152		50	Transfer pressure part	253 838
19	Selection cam on the left E10-18	251 876		51	Offering cam	210 185
20	Selection cam on the right E10-18	251 877		500	Cap screw M4x8	020 091
21	Selection cam E10-18	251 875		510	Cap screw M3x8	020 081



5.18 Cam box E12m.10


Notes:

6 Main take-down




6.1 Main take-down

Pos	Designation	ID		Pos	Designation	ID
Σ	Main take-down					
1	Main take-down on the left	253 851		3	Main take-down in the middle E10 E12 E14 E6.2(12m.10) E6.2 E7.2 E14/12	253 525
2	Main take-down on the right	253 852			Main take-down in the middle E16 E18 E8.2	253 593



6.1.1 Main take-down on the left


Pos	Designation	ID		Pos	Designation	ID
Σ	Main take-down on the left	253 851				
2	Bearing race complete	244 459		17	Spring bolt	221 143
3	Shaft on the left at the rear	221 012		19	Stop point	252 503
5	Bolts	208 538		500	Screw 50x15	251 728
7	Mounting plate on the left complete	231 725		504	Washer18	023 295
9	Swivel-mounted bearing	251 761		505	Locking ring18x1,2	020 955
10	Full floating axle on the left	251 984		511	Cap screwM6x12	020 134



6.1 Main take-down


6.1.1.1 Swivel-mounted bearing

Pos	Designation	ID		Pos	Designation	ID
Σ	Swivel-mounted bearing	251 761				
1	Swivel-mounted bearing	241 996		500	Screw M35x10	259 102
2	Sheet metal support	251 749		504	Circlip4	021 020
3	Axle	251 758		505	Tension spring 21x3,0x192	240 217



6.1.2 Main take-down on the right


Pos	Designation	ID		Pos	Designation	ID
Σ	Main take-down on the right	253 852				
1	Clutch set	251 677		20	Threaded bush	222 522
2	Bearing race complete	244 459		500	Screw 50x15	251 728
5	Bolts	208 538		504	Washer18	023 295
8	Mounting plate on the right complete	240 069		505	Locking ring18x1,2	020 955
9	Swivel-mounted bearing	251 761		511	Cap screwM6x12	020 134
10	Full floating axle on the right	251 985		515	Microswitch Xgk2-s21 250	210 510
17	Spring bolt	221 143		516	Cap screwM3x20	023 221
19	Stop point	252 503		517	Washer3	023 657



6.1 Main take-down


6.1.2.1 Mounting plate

Pos	Designation	ID		Pos	Designation	ID
Σ L	Mounting plate on the left complete	231 725		Σ R	Mounting plate on the right complete	240 069
1	Mounting plate on the left	231 541		1	Mounting plate on the right	240 068
2	Retaining plate on the left	231 539		2	Shoulder screw	240 067
500	Pan-head screwM5x10	023 247		3	Retaining plate on the right	240 066
501	Serrated lock washer J5,3	022 489		500	Hexagon nut M4-6	022 536
				501	Microswitch	026 259
				502	Cap screwM3x16	022 583
				503	Cap screwM5x8	244 278
				504	Washer5-200	020 871



6.1.2.2 Full floating axle


Pos	Designation	ID		Pos	Designation	ID
Σ L	Full floating axle on the left	251 984		Σ R	Full floating axle on the right	251 985
1	Shaft on the left at the front	221 013		1	Eccentric	251 959
2	Eccentric	251 959		2	Shaft on the right	223 393
500	Set collar	020 938		3	Gear wheel Z=40, M=2	213 744
502	Fitting freewheel ZZ6203L	023 294		500	Fitting freewheel ZZ6203L	023 294
900	Setscrew M6x8	022 684		501	Set collar	020 938
				502	Setscrew M6x8	022 684
				503	Feather key A 6x6x25	023 017



6.1 Main take-down


6.1.3 Main take-down in the middle

Pos	Designation	ID		Pos	Designation	ID
Σ	Main take-down in the middle			13	Take-down roller at the rear complete	
	E10 E12 E14 E6.2(12m.10) E6.2 E7.2 E14/12	253 525			E10 E12 E14 E6.2(12m.10) E6.2 E7.2 E14/12	253 853
	E16 E18 E8.2	253 593			E16 E18 E8.2	253 854
4	Stripper angle at the rear complete	240 125		509	Cap screwM8x25	020 142
12	Motor take-down unit complete	253 803		18*	Stop point	253 432
15	Take-down roller at the front complete	241 426		512*	Washer6	020 881
20	Connection cable winding plate	241 703		513*	Pan-head screwM6x16	023 124



6.1.3.1 Stripper angle


Pos	Designation	Id		Pos	Designation	Id
Σ	Stripper angle at the rear complete	240 125				
1	Stripper angle	240 126		5	Adjustment weight	229 248
2	Shaft	240 127		500	Cap screwM5x8	023 319
3	Cam	209 278		501	Set collar	020 934
4	Bolts	228 310		502	Setscrew M5x6	022 738



6.1 Main take-down


6.1.3.2 Rear take-down roller

Pos	Designation	ID	Pos	Designation	ID
Σ	Take-down roller at the rear complete		1	Roller	
	E10 E12 E14 E6.2(12m.10) E6.2 E7.2	243 810		E10 E12 E14 E6.2(12m.10) E6.2 E7.2	206 770
	E16 E18 E8.2 mg	243 889		E16 E18 E8.2 mg	231 400
2	Stripper	241 612	10c	Ring	222 895
3	Shaft	237 190	9	Stop ring on the left	222 910
4	Ring on the left	255 830	11	Brush	225 819
5	Ring on the right	255 831	12	Rod	237 192
6	Spacer slide	222 062	500	Setscrew	258 910
7	Stop ring on the left	204 369	501	Dowel pin 6x32	020 685
8	Spacer slide	240 104	510	Grooved ball bearing 16007	021 697
10	Support	232 578	511	Slide bearing GFM-101216-06	023 280
10a	Supporting plate	232 512	512	Slide bearing GFM-101216-09	023 356
10b	Bearing	232 571			



6.1.3.3 Front take-down roller


Pos	Designation	Id		Pos	Designation	Id
Σ	Take-down roller at the front complete	241 426		4	Locating piece	221 935
1	Take-down roller at the front	221 243		500	Compression spring 1x10x30	023 741
2	Angle rail complete	241 425		501	Cap screwM5x12	020 132
3	Pressure sleeve	220 911		502	Washer5-200	020 880



6.1 Main take-down


6.1.3.3.1 Front roller elements

Pos	Designation		Id		Pos	Designation		Id
Σ	Take-down roller at the front		221 243					
1	Bearing support on the left complete		221 225		4	Roller		220 905
	aa	Universal joint	221 137		5	Tube		221 092
	ab	adaptor	221 132		6	Bearing support on the right complete		221 240
	b	Bearing support	220 913			aa	Universal joint	221 137
	c	Gear wheel	220 910			ab	adaptor	221 132
	501	Spring dowel sleeve 4x20	023 551			b	Bearing support	220 913
	510	Cap screwM5x20	020 133			c	Gear wheel	220 910
	511	Washer5	023 542			501	Spring dowel sleeve 4x20	023 551
			510			Cap screwM5x20	020 133	
			511			Washer5	023 542	
2	Support		251 557		7	Spacer pipe on the right		253 407
3	Bearing support complete		221 241		8	Spacer pipe on the left		253 408
	3b	Bearing support	220 913		500	Circlip		021 025
	3a	Gear wheel	220 910					
	530	Hexagon nut M5	023 541					
	531	Washer5-100hv	023 542					
	532	Cap screwM5x30	022 396					



6.1.3.3.2 Pressure angle rail

Pos	Designation	Id		Pos	Designation	Id
Σ	Angle rail complete	241 425		500	Washer6-200	022 431
1	Switch complete with cable	221 265		501	Hexagon nut M5-8	023 541
2	Spring flange	242 327		502	Compression spring 0,8x9,2x27,5	023 537
3	Angle rail	241 773		503	Cap screwM2x12	023 522
4	Winding plate	221 101		504	Washer2-200	022 908
5	Locking ring	242 325		505	Shoulder screw M5x20x5	023 675




Notes:

7 Auxiliary take-down




7.1 Auxiliary take-down pre-assembled

Pos	Designation	Id		Pos	Designation	Id
Σ	Auxiliary take-down pre-assembled	254 061				
1	Bearing on the right complete	239 996		14	Lever at the rear on the right	227 260
2	Bearing on the left complete	239 999		15	Toothed belt pulley complete	226 708
4	Guide plate	213 362		16	Bolts	227 914
5	Metal angle on the left complete	225 013		17	Protective plate	225 754
6	Metal angle on the right complete	225 014		502	Shoulder screw M3x27x32	023 634
9	Toothed belt10T5/260	208 832		504	Set collar	020 934
10	Take-down roller	224 891		505	Stop disk	023 646
11	Lever at the front on the left	227 263		506	Spring dowel sleeve 3x20	020 776
12	Lever at the front on the right	227 262		507	Sheet metal screw St4,8x22-	023 259
13	Lever at the rear on the left	227 261		520*	Cap screw M6x12	020 134



7.1.1 Right bearing of the auxiliary take-down


Pos	Designation	Id	Pos	Designation	Id
Σ	Bearing on the right complete		532	Slide bearing GFM-081014-06	023 358
20	Bearing block on the right	258 913	34	Roller deflector	218 805
21	Cover	257 466	500	Cap screw M3x16	022 560
22	Drive shaft complete	227 857	510	Cap screw M3x20	022 448
23	Drive shaft complete	227 853	511	Pan-head screw M4x10	023 450
24	Gear wheel M=1,5, Z=20	213 880	512	Countersunk head screw M4x12	023 062
25	Gear wheel M=1,5, Z=20	210 504	513	Hexagon nutM6-6	020 836
26	Gear wheel on the right complete	218 524	514	Threaded bolt with shoulder	243 226
27	Gear rack on the right	253 487	515	Shoulder screw M4x9x14	020 602
28	Threaded spacer	229 683	516	SetscrewM6x16-45	023 092
29	Sleeve	227 257	517	Spiral pin 4x24	023 544
30	Sleeve	239 997	518	Shim ring 4x8x0,5	023 384
31	Collar bolt	210 551	519	Shim ring 10x16x1,5	023 261
32	Cable with switch auxiliary take-downokc	243 142	520	Locking ring26x1,2	023 359
33	Connecting rod complete	226 710	521	Fastening clip 255/5,2	008 335
	33a	Connecting rod	522	Tension spring 7,5x0,7x28	023 595
	531	Needle bearingHK1010	523	Grooved ball bearing 6000-2Z	022 599



7.1 Auxiliary take-down pre-assembled


7.1.2 Left bearing of the auxiliary take-down

Pos	Designation	Id		Pos	Designation	Id
Σ	Bearing on the left			41	Gear wheel on the left complete	218 523
21	Cover	257 466		42	Gear rack on the left	253 488
28	Threaded spacer	229 683		510	Cap screw M3x20	022 448
30	Sleeve	239 997		512	Countersunk head screw M4x12	023 062
31	Collar bolt	210 551		513	Hexagon nut M6-6	020 836
33	Connecting rod complete	226 710		514	Threaded bolt with shoulder	243 226
	33a Connecting rod	255 696		515	Shoulder screw M4x9x14	020 602
	530 Slide bearing GFM-081014-06	023 358		516	Setscrew M6x16-45	023 092
	531 Needle bearing HK1010	023 664		518	Shim ring 4x8x0,5	023 384
34	Roller deflector	218 805		519	Shim ring 10x16x1,5	023 261
36	Bearing block on the left	258 914		520	Locking ring 26x1,2	023 359
37	Drive shaft complete	227 887		522	Tension spring 7,5x0,7x28	023 595
39	Bolts	226 705		523	Grooved ball bearing 6000-2Z	022 599




7.1.3 Metal angle on the left and right complete

Pos	Designation	Id		Pos	Designation	Id
Σ L	Metal angle on the left complete	225 013		Σ R	Metal angle on the right complete	225 014
1	Metal angle on the left	224 920		1	Metal angle on the right	224 931
2	Roller deflector	218 805		2	Roller deflector	218 805
3	Fine rope	224 977		3	Fine rope	224 977
4	Sleeve	227 867		4	Sleeve	227 867
500	Cap screwM3x16	022 560		500	Cap screwM3x16	022 560
501	Hexagon nut M3-6	022 564		501	Hexagon nut M3-6	022 564
502	Shim ring 4x8x0,5	023 384		502	Shim ring 4x8x0,5	023 384
503	Spring washer A3	021 005		503	Spring washer A3	021 005
507	Tension spring 8x0,9x75	021 287		507	Tension spring 8x0,9x75	021 287




7.2 Auxiliary take-down in the middle

Pos	Designation	Id		Pos	Designation	Id
Σ	Auxiliary take-down in the middle	254 062				
3	Take-down motor complete auxiliary take-down	214 449		8	Detent plate	222 040
7	Shoulder screw	207 101		500	Cap screwM6x12	020 134



7.3 Motor


Pos	Designation	Id		Pos	Designation	Id
Σ	Motor auxiliary take-down complete	214 449		8	Shaft	219 025
1	Motor auxiliary take-down	213 871		500	Cap screwM3x6	022 589
2	Motor bracket	218 040		501	Setscrew M6x10	023 543
3	Drive sleeve	219 024		502	Cap screwM5x55	023 321
4	Impulse disc	218 449		503	Compression spring 0,63x10,97x40	023 500
5	Gear unit 4GN36K	220 353		504	Shim ring 6x12x1	023 444
7	Light barrier Auxiliary take-down	217 462		508	Dowel pin 5x28	241 686



7.4 Yarn brake at clamping and cutting bed

7.4 Yarn brake at clamping and cutting bed

Pos	Designation	Id		Pos	Designation	Id
Σ L	Yarn brake on the left	256 740		Σ R	Yarn brake on the right	256 715
1	Cover on the left	256 739		3	Cover on the right	256 714
2	Leaf spring	256 712		1	Leaf spring	256 712
3	Test clamping plate	256 713		2	Test clamping plate	256 713
500	Cap screwM4x6	023 067		500	Cap screwM4x6	023 067




8 Comb take-down




8.1 Comb take-down

Pos	Designation	ID		Pos	Designation	ID
Σ	Comb take-down					
1	Comb take-down on the left	256 834		3	E12 E6.2 E6.2(12m.10)	253 522
2	Comb take-down on the right	256 835			E14 E7.2 E14/12	253 590
3	Comb take-down in the middle				E16 E8.2	253 591
	E10	253 589			E18	253 592



8.2 Comb take-down on the left


Pos	Designation	Id	Pos	Designation	Id
Σ	Comb take-down on the left	256 834			
1	Clamping piece	209 379		528 Hexagon nut M8-6	020 838
2	Pressure plate	241 967	34	Swivel lever on the left	252 859
3	Bolts	222 152	36	Clamping plate	227 159
5	Toothed belt16T10/1300	240 065	500	Cap screwM6x16	020 135
6	Eccentric pin	222 320	507	Cap screwM6x65	240 162
11	Bolts	207 689	508	Cap screwM6x45	022 689
14	Toothed lock washer at the bottom complete	211 822	511	Hexagon nut M5-8	023 541
15	Toothed lock washer at the top complete	211 823	512	Hexagon nut M5-6	020 835
17	Stay bolt	222 315	513	Hexagon nut M6-6	020 836
18	Stay bolt	240 056	514	Hexagon nut M8-6	020 838
19	Threaded rod M5	240 057	515	Hexagon nut M16-6	020 845
25	Reflector complete	256 826	517	Washer16	020 876
26	Guide bar C35	206 560	524	Locking ring17x1	023 299
27	Rubber buffer	206 561	530	Tension spring Din2097 15x1,50x70,94	251 614
28	Comb guide on the left	255 425	531	Cap screwM6x12	020 134
28a	Driving bolt	255 427	540*	Pan-head screwM5x10	023 247



8.3 Comb take-down on the right


8.3 Comb take-down on the right

Pos	Designation	Id	Pos	Designation	Id
Σ	Comb take-down on the right	256 835			
1	Clamping piece	209 379	529	Hexagon nut M8-6	020 838
2	Pressure plate	241 967	33	Swivel lever on the right	252 858
3	Bolts	222 152	36	Clamping plate	227 159
5	Toothed belt16T10/1300	240 065	500	Cap screwM6x16	020 135
6	Eccentric pin	222 320	507	Cap screwM6x65	240 162
12	Drive shaft comb complete	214 583	508	Cap screwM6x45	022 689
14	Toothed lock washer at the bottom complete	211 822	511	Hexagon nut M5-8	023 541
17	Stay bolt	222 315	512	Hexagon nut M5-6	020 835
18	Stay bolt	240 056	513	Hexagon nut M6-6	020 836
19	Threaded rod M5	240 057	514	Hexagon nut M8-6	020 838
22	Proximity switch inductive at the top	231 516	515	Hexagon nut M16-6	020 845
23	Proximity switch inductive at the bottom	231 520	517	Washer16	020 876
24	Light barrier complete	256 825	530	Tension spring 15x1,50x70,94	251 614
26	Guide bar C35	206 560	531	Cap screwM6x12	020 134
27	Rubber buffer	206 561	532	Washer6	020 872
29	Comb guide on the right	255 424	533*	Shim 0,2x12x27	023 735
29a	Driving bolt	255 427	534*	Shim 0,5x12x27	023 736
29b	Angle	240 112	540*	Pan-head screwM5x10	023 247



8.3.1 Drive shaft of comb


Pos	Designation	Id		Pos	Designation	Id
Σ	Drive shaft comb complete	214 583				
1	Shaft	213 969		500	Feather key A 6x6x25	023 017
2	Gear wheel Z=40, M=2	213 744		502	Setscrew M6x8	022 684
	Always order position 502 additionally			503	Setscrew M6x12	023 898
3	Toothed belt pulley at the top	206 394		504	Set collar	020 938
	Always order position 503 additionally					



8.3 Comb take-down on the right


8.3.2 Swivel lever comb take-down

Pos	Designation	Id		Pos	Designation	Id
Σ L	Swivel lever on the left	252 859		Σ R	Swivel lever on the right	252 858
1	Support	252 780		1	Support	252 780
2	Shaft	223 994		2	Shaft	238 339
4	Plunger	255 650		3	Microswitch	026 259
5	Swivel lever	239 248		4	Plunger	255 650
6	Bolt	214 053		5	Swivel lever	239 248
7	Eccentric bolt	255 651		6	Bolt	214 053
500	Compression spring 1,4x13,6x93	023 572		7	Angle	224 009
501	Spring dowel sleeve Iso8752-5x20	020 794		8	Angle	238 304
502	Dowel pin 5x22	023 716		9	Eccentric bolt	255 651
504	Shoulder screw M5x29x35	251 618		500	Pan-head screwM5x10	023 247
505	Shoulder screw M5x5,8x6,2	023 365		501	Spring dowel sleeve 5x20	020 794
507	Washer10	020 884		502	Dowel pin 5x22	023 716
508	Locking ring	020 950		503	Spring dowel sleeve 5x12	020 793
509	Shoulder screw M5x12x18	020 539		504	Shoulder screw M5x29x35	251 618
511	Hexagon nut M8-6	020 838		505	Shoulder screw M5X5,8X6,2	023 365
				506	Cap screwM4x8	022 501
				507	Washer10	020 884
				508	Locking ring 10x1	020 950
				509	Shoulder screw M5X12X18	020 539
				510	Cap screwM3x16	022 583
				511	Washer3	020 877
				513	Hexagon nut M8-6	020 838



8.4 Comb take-down in the middle


Pos	Designation	ID		Pos	Designation	ID
Σ	Comb take-down in the middle			31	Comb unit	
	E10	253 589			E10	241 533
	E12 E6.2 E6.2(12m.10)	253 522			E12 E6.2 E6.2(12m.10)	240 061
	E14 E7.2 E14/12	253 590			E14 E7.2 E14/12	241 534
	E16 E8.2	253 591			E16 E8.2	241 535
	E18	253 592			E18	241 536
8	Flange	207 695		32	Motor take-down unit complete	253 803
9	Shaft long	213 968		35	Guide plate	259 237
500	Cap screwM6x16	020 135		502	Cap screwM8x25	020 142
501	Pan-head screwM5x10	023 247		525	Serrated lock washer J5,3	022 489



8.4 Comb take-down in the middle


8.4.1 Comb unit

Pos	Designation	ID		Pos	Designation	ID
Σ	Comb unit			5	Hook slider	
	E10	241 533			E10	220 996
	E12 E6.2 E6.2(12m.10)	240 061			E12 E16 E6.2 8.2 E6.2(12m.10)	220 994
	E14 E7.2 E14/12	241 534			E14 E7.2 E14/12	220 993
	E16 E8.2	241 535			E18	220 997
	E18	241 536				
1	Hook bed			7	Collar bolt complete	211 036
	E10	221 196		8	Cross slider	213 429
	E12 E6.2 E6.2(12m.10)	221 197		9	Cover rail	222 866
	E14 E7.2 E14/12	221 198		10	Plunger	205 678
	E16 E8.2	221 199		11	Switching lever complete	240 060
	E18	221 200		15	Stabilizator	215 253
2	Closer			500	Cap screw M4x30	023 290
	E10 E12 E14 E6.2 E7.2 E6.2(12m.10) E14/12	230 106		502	Countersunk head screw M5x12	023 340
	E16 E18 E8.2	230 107		504	Hexagon nut M4-8	023 046
3	Body			505	Hexagon nut M5-04	020 854
	E10 E12 E14 E6.2 E7.2 E6.2(12m.10) E14/12	230 094		508	Washer5	020 871
	E16 E18 E8.2	230 095		510	Cap screw M4x35	023 550
4	Cover rail	213 428		511	Circlip	022 774



8.4.2 Switching lever comb take-down


Pos	Designation	ID		Pos	Designation	ID
Σ	Switching lever complete	240 060		500	Cap screwM3x25	023 093
1	Screw-on plate on the right	240 058		501	Cap screwM4x20	023 171
2	Screw-on plate on the left	240 059		502	Cap screwM4x16	023 123
3	Lever	215 228		504	Pan-head screw M6x12	023 435
4	Bearing bolt	215 675		505	Pan-head screw M5x16	023 417
5	Eccentric	205 681		506	Shim ring 16x22x2	023 449
6	Tension cam	215 287		507	Shim ring 10x16x1	023 260
13	Intermediate plate	213 980		510	Hexagon nut M5	020 854
14	Holding plate	218 977		511	Collar bearing 10x16x22	022 841
15	Motor comb hook with 2 phases	244 635		515	Threaded spacer	210 488



8.4 Comb take-down in the middle

Notes:


9 Yarn delivery device



9.1 Yarn guide system from 14 up to 16 FKE


9.1 Yarn guide system from 14 up to 16 FKE

Pos	Designation	ID		Pos	Designation	ID
Σ	Yarn guide system 14 FKE	241 587				
	Yarn guide system 16 FKE	241 550		8	Yarn guide bracket complete	241 581
1	Support 50"	243 110		11	Slot nut	228 851
2	Yarn control device(FKE)	237 124		501	Self-locking screw M6x12	023 415
3	Connection cable FKE 50" ECO	254 056		502	Screw M6x20	023 721
4	Yarn guide bar	240 324		503	Serrated nut M6-10	023 414
5	Support on the right	251 629		505	Washer6-200	022 431
6	Support on the left	251 630		506	Pan-head screw M8x16	023 113
7	Support	243 792		508	Serrated lock washer	023 388




9.2 Yarn guide system with 18 and 20 FKE

Pos	Designation	ID		Pos	Designation	ID
Σ	Yarn guide system 18 FKE	240 322		9	Support on the left	243 602
	Yarn guide system 20 FKE	241 599		10	Support on the right	243 603
1	Support	243 110		11	Slot nut	228 851
2	Yarn control device(FKE)	237 124		501	Self-locking screw M6x12	023 415
3	Connection cable FKE 50" ECO	254 056		502	Screw M6x20	023 721
4	Yarn guide bar	240 324		503	Serrated nut M6-10	023 414
5	Support on the right	251 629		505	Washer6	022 431
6	Support on the left	251 630		506	Pan-head screw M8x16	023 113
7	Support	239 295		507	Square nut M8	023 269
8	Yarn guide bracket complete	241 581		508	Serrated lock washer	023 388




9.3 Yarn control device

Pos	Designation	Id		Pos	Designation	Id
Σ	Yarn control device	237 124				
1	Lamp cap	251 166		13	Tension spring	253 040
2	Turning knob	251 167		14	Tension spring	253 041
3	Knot detector for large knots	251 168		15	Ceramic eyelet open	240 733
4	Knot detector for mall knots	251 169		16	Stop bow	253 043
5	Screw	251 170		17	Jack	253 046
6	Yarn brake disk	216 365		18	Contact pin	253 047
7	Yarn holder	244 407		19	Contact pin	253 048
8	Sleeve	253 034		20	Contact pin	253 049
9	Compression spring	253 035		21	Contact pin	253 050
10	Pencil	253 036		22	Compression spring	253 055
11	Trip cam	253 037		23	Turning knob	253 056
12	Tension spring	253 038		24	Disk	216 372



9.4 Left yarn guide
E10|E12|E14|E6.2(12m.10)|E14/12 |E7.2


Pos	Designation	ID		Pos	Designation	ID
Σ	Safety door on the left complete E10-18	241 273		15	Ground cable	244 404
6	Wave	241 318		17	Stop bar on the left complete	258 454
7	Yarn tensioner on the left completeE10-18	241 365		20*	Stopping device 12-fold on the left complete	260 342
8	Cover plate 16-fold	259 400		501	Ceramic eyelet	240 640
9	Wire bow on the left	241 370		504	Washer6	022 537
10	Yarn deflector	242 011		510	Screw KB 60x20	237 682
11	Connection cable yarn tensionerokc	240 808		512	Flat connector 2x45° M6	243 117



9.4 Left yarn guide E10 | E12 | E14 | E6.2(12m.10) | E14/12 | E7.2

9.4.1 Yarn tensioner on the left
E10 | E12 | E14 | E16 | E18 | E14/12 | E6.2(12m.10) | E7.2 | E8.2


Pos	Designation	ID		Pos	Designation	ID
Σ	Yarn tensioner on the left completeE10-18	241 365				
1	Card yarn tensioner 16-fold on the left	241 345		8	Grounding plate of tension axle	243 121
2	Tension axle on the left complete E10-18	241 381		9	Ground cable yarn tensioner okc	243 105
3	Housing	241 367		500	Screw KB 30x8	236 228
4	Slider	241 694		501	Circlip	021 022
5	Stop point	241 368		502	Tension spring 4,9x0,45x53	023 504
6	Border	242 268		503	Circlip	021 020
7	Spacer	242 048		504	Countersunk screw M4x10	241 914



9.4 Left yarn guide E10 | E12 | E14 | E6.2(12m.10) | E14/12 | E7.2


9.4.1.1 Tension axle on the left E10 | E12 | E14 | E16 | E18 | E14/12 | E6.2(12m.10) | E7.2 | E8.2

Pos	Designation	ID	Pos	Designation	ID
Σ	Tension axle on the left complete E10-18	241 381	Σ 5	Thread clamp AKF	238 695
1	Axle	243 107	51	HousingAKF	238 689
2	Tension arm pre-assembledE10-18	258 459	52	Cover AKF	237 926
6	Wire bow	238 694	53	Sheet metal at the bottom (housing AKF)	240 719
500	Shim ring 8x14x0,5	023 501	54	Lever AKF	238 692
501	Circlip	021 022	55	Pressure piece AKF	238 690
502	Grooved pin 2x6	243 172	56	SliderAKF	238 691
			57	Wire bow	238 694
			58	Wire	237 940
			551	Screw KB 35x12	237 681
			552	Screw KB 40x8	236 227
			553	Compression spring0,30x4,50x18,50	241 437
			554	Grooved pin 2x6	243 172




9.4.2 Yarn deflector

Pos	Designation	ID		Pos	Designation	ID
Σ	Yarn deflector	242 011				
1	Support of yarn deflector	242 009		2	Ceramic eyelet open	240 733




9.4.3 Stopping device on the left

Pos	Designation	Id		Pos	Designation	Id
Σ	Stopping device 12-fold on the left complete	260 342		500	Eyelet 4,2	021 502
1	Yarn brakeE10-18	259 440		501	Clamping ring for sintered ceramics eye	259 606
2	Support plate on the left	260 288		510*	Pan-head screw M5x10	023 247




9.5 Yarn guide on the left E16 | E18 | E8.2

Pos	Designation	Id		Pos	Designation	Id
Σ	Safety door on the left complete E16-18	259 725				
5	Yarn brake complete	244 347		14	Clamping bow	244 409
6	Wave	241 318		15	Ground cable	244 404
7	Yarn tensioner on the left completeE10-18	241 365		17	Stop bar on the left complete	258 454
8	Cover	240 783		501	Ceramic eyelet	240 640
9	Wire bow on the left	241 370		502	Compression spring0,90x5,40x13,60	241 360
10	Yarn deflector	242 011		504	Washer6	022 537
11	Connection cable yarn tensionerokc	240 808		510	Screw KB 60x20	237 682
13	Yarn brake not adjustable	244 356		512	Flat connector 2x45° M6	243 117




9.5.1 Yarn brake and yarn deflector

Pos	Designation	ID		Pos	Designation	ID
A	Yarn brake complete	244 347		B	Yarn deflector	242 011
1	Support	240 607		1	Support of yarn deflector	242 009
2	Slider	240 606		2	Ceramic eyelet open	240 733
3	Brake disk	244 355				
4	Ceramic eyelet open	243 778				
500	Compression spring 0,65x20,15x14,80	241 361				
501	O-ring 11x2	241 434				




9.6 Left yarn guide E6.2

Pos	Designation	ID	Pos	Designation	ID
Σ	Safety door on the left complete E7-8	241 272			
5	Yarn brake complete	244 347	14	Clamping bow	244 409
6	Shaft	241 318	15	Ground cable	244 404
7	Yarn tensioner on the left completeE7-8	241 364	17	Stop bar on the left complete	258 454
8	Cover	240 783	501	Ceramic eyelet	240 640
9	Wire bow on the left	241 370	502	Compression spring 0,90x5,40x13,60	241 360
10	Yarn deflector	242 011	504	Washer6	022 537
11	Connection cable yarn tensionerokc	240 808	510	Screw KB 60x20	237 682
13	Yarn brake not adjustable	244 356	512	Flat connector 2x45° M6	243 117



9.6.1 Left yarn tensioner E6.2


Pos	Designation	ID		Pos	Designation	ID
Σ	Yarn tensioner on the left complete E7-8	241 364				
1	Card yarn tensioner 16-fold on the left	241 345		7	Spacer	242 048
2	Tension axle on the left complete E3-8	241 366		8	Grounding plate of tension axle	243 121
3	Housing	241 367		9	Ground cable yarn tensioner okc	243 105
4	Slider	241 694		500	Screw KB 30x8	236 228
5	Stop point	241 368		501	Circlip	021 022
6	Border	242 268		502	Tension spring 4,9x0,5x53 E6.2	023 503
504	Countersunk screw M4x10	241 914		503	Circlip	021 020



9.6 Left yarn guide E6.2


9.6.1.1 Left tension axle E6.2

Pos	Designation	ID		Pos	Designation	ID
Σ	Tension axle on the left complete E3 – 8	241 366		Σ 5	Thread clamp AKF	238 695
1	Axle	243 107		51	HousingAKF	238 689
2	Tension arm pre-assembled E3-8	259 448		52	Cover AKF	237 926
6	Wire bow	238 694		53	Sheet metal at the bottom (housing AKF)	240 719
500	Shim ring 8x14x0,5	023 501		54	Lever AKF	238 692
501	Circlip	021 022		55	Pressure piece AKF	238 690
502	Grooved pin 2x6	243 172		56	SliderAKF	238 691
				57	Wire bow	238 694
				58	Wire	237 940
				551	Screw KB 35x12	237 681
				552	Screw KB 40x8	236 227
				553	Compression spring0,30x4,50x18,50	241 437
				554	Grooved pin 2x6	243 172



9.7 Right yarn guide E10 | E12 | E14 | E6.2(12m.10) | E7.2


Pos	Designation	Id		Pos	Designation	Id
Σ	Safety door on the right complete E10-18	241 276		15	Ground cable	244 404
6	Wave	241 318		17	Stop bar on the right complete	258 562
7	Yarn tensioner on the right complete E10-18	241 384		20*	Stopping device 12-fold on the right complete	260 341
8	Cover plate 16-fold	259 400		501	Ceramic eyelet	240 640
9	Wire bow on the right	241 369		504	Washer6	022 537
10	Yarn deflector	242 011		510	Screw KB 60x20	237 682
11	Connection cable yarn tensionerokc	240 808		512	Flat connector 2x45° M6	243 117



9.7 Right yarn guide E10|E12|E14|E6.2(12m.10)|E7.2

9.7.1 Yarn tensioner on the right
E10|E12|E14|E16|E18|E14/12|E6.2(12m.10)|E7.2|E8.2


Pos	Designation	Id		Pos	Designation	Id
Σ	Yarn tensioner on the right complete E10-18	241 384				
1	Card yarn tensioner 16-fold on the right	241 346		8	Grounding plate of tension axle	243 121
2	Tension axle on the right completeE10-18	241 380		9	Ground cable yarn tensioner okc	243 105
3	Housing	241 367		500	Screw KB 30x8	236 228
4	Slider	241 694		501	Circlip	021 022
5	Stop point	241 368		502	Tension spring 4,9x0,45x53	023 504
6	Border	242 268		503	Circlip	021 020
7	Spacer	242 048		504	Countersunk screw M4x10	241 914



9.7 Right yarn guide E10 | E12 | E14 | E6.2(12m.10) | E7.2


9.7.1.1 Tension axle on the right E10 | E12 | E14 | E16 | E18 | E14/12 | E6.2(12m.10) | E7.2 | E8.2

Pos	Designation	ID	Pos	Designation	ID
Σ	Tension axle on the right completeE10-18	241 380	Σ 5	Thread clamp AKF	238 695
1	Axle	243 107	51	HousingAKF	238 689
2	Tension arm pre-assembled	258 459	52	Cover AKF	237 926
6	Wire bow	238 694	53	Sheet metal at the bottom (housing AKF)	240 719
500	Shim ring 8x14x0,5	023 501	54	Lever AKF	238 692
501	Circlip	021 022	55	Pressure piece AKF	238 690
502	Grooved pin 2x6	243 172	56	SliderAKF	238 691
			57	Wire bow	238 694
			58	Wire	237 940
			551	Screw KB 35x12	237 681
			552	Screw KB 40x8	236 227
			553	Compression spring0,30x4,50x18,50	241 437
			554	Grooved pin 2x6	243 172




9.7.2 Stopping device on the right

Pos	Designation	Id		Pos	Designation	Id
Σ	Stopping device 12-fold on the right complete	260 341		500	Eyelet 4,2	021 502
1	Yarn brakeE10-18	259 440		501	Clamping ring for sintered ceramics eye	259 606
2	Support plate on the right	260 287		510*	Pan-head screw M5x10	023 247



9.8 Right yarn guide E16 | E18 | E8.2


Pos	Designation	Id	Pos	Designation	Id
Σ	Safety door on the right complete E10-18	259 726			
5	Yarn brake complete	244 347	14	Clamping bow	244 409
6	Wave	241 318	15	Ground cable	244 404
7	Yarn tensioner on the right complete E10-18	241 384	17	Stop bar on the right complete	258 562
8	Cover	240 783	501	Ceramic eyelet	240 640
9	Wire bow on the right	241 369	502	Compression spring0,90x5,40x13,60	241 360
10	Yarn deflector	242 011	504	Washer6	022 537
11	Connection cable yarn tensionerokc	240 808	510	Screw KB 60x20	237 682
13	Yarn brake not adjustable	244 356	512	Flat connector 2x45° M6	243 117



9.9 Right yarn guide E6.2


9.9 Right yarn guide E6.2

Pos	Designation	Id		Pos	Designation	Id
Σ	Safety door on the right complete E7-8	241 275		13	Yarn brake not adjustable	244 356
5	Yarn brake complete	244 347		14	Clamping bow	244 409
6	Shaft	241 318		15	Ground cable	244 404
7	Yarn tensioner on the right complete E7-8	241 383		501	Ceramic eyelet	240 640
8	Cover	240 783		502	Compression spring 0,90x5,40x13,60	241 360
9	Wire bow on the right	241 369		504	Washer6	022 537
10	Yarn deflector	242 011		510	Screw KB 60x20	237 682
11	Connection cable yarn tensionerokc	240 808		512	Flat connector 2x45° M6	243 117



9.9.1 Right yarn tensioners E6.2


Pos	Designation	Id		Pos	Designation	Id
Σ	Yarn tensioner on the right complete E7-8	241 383				
1	Card yarn tensioner 16-fold on the right	241 346		8	Grounding plate of tension axle	243 121
2	Tension axle on the right completeE3-8	241 379		9	Ground cable yarn tensioner okc	243 105
3	Housing	241 367		500	Screw KB 30x8	236 228
4	Slider	241 694		501	Circlip	021 022
5	Stop point	241 368		502	Tension spring 4,9x0,5x53	023 503
6	Border	242 268		503	Circlip	021 020
7	Spacer	242 048		504	Countersunk screw M4x10	241 914



9.9 Right yarn guide E6.2


9.9.1.1 Right tension axle E6.2

Pos	Designation	ID	Pos	Designation	ID
Σ	Tension axle on the right completeE3-8	241 379	Σ 5	Thread clamp AKF	238 695
1	Axle	243 107	51	HousingAKF	238 689
2	Tension arm pre-assembled E3-8	259 448	52	Cover AKF	237 926
6	Wire bow	238 694	53	Sheet metal at the bottom (housing AKF)	240 719
500	Shim ring 8x14x0,5	023 501	54	Lever AKF	238 692
501	Circlip	021 022	55	Pressure piece AKF	238 690
502	Grooved pin 2x6	243 172	56	SliderAKF	238 691
			57	Wire bow	238 694
			58	Wire	237 940
			551	Screw KB 35x12	237 681
			552	Screw KB 40x8	236 227
			553	Compression spring0,30x4,50x18,50	241 437
			554	Grooved pin 2x6	243 172



9.10 Bobbin board


Pos	Designation		ID		Pos	Designation		ID
Σ	Table complete 50"		240 241					
1	Table		251 244		18	Positioning pin		204 819
4	Support element		228 594		24	Energy chain display 38 links		253 888
10	Magnet switch safety door		219 983		31	Cable USB extension		253 706
11	Magnet switch safety door		220 159		508	Pan-head screwM3x8		023 251
13	Guide rail at the top complete		257 485		520	Washer		020 901
17	Lamp at the top complete		222 509		20*	Support of left feed wheel		250 966
	17a	Light 230 V 50/60 Hz	205 546		21*	Support of right feed wheel		250 967
	17b	Clamping bow	209 504		22*	Slot nut		228 851
	17c	Cellular caoutchouc 40x20	208 018		520*	Pan-head screwM8x16		023 113
	17d	Lamp support	221 951		521*	Pan-head screwM8x18		251 331



9.11 Bar unit


9.11 Bar unit

Pos	Designation		ID		Pos	Designation		ID
Σ	Bar unit		250 971			530	Eyelet 4,2	021 502
1	Yarn carrier rail		255 464			531	Clamping ring	259 606
2	FF support		252 010			532	Pan-head screw M5x8	239 408
3	Yarn guide bracket complete		259 403			930	Pan-head screw M6x10	023 183
	31	Eyelet holder complete	259 402		500	Cap screw M6x35		020 139
	32	Holding angle	259 574		900	Cap screw M8x25		020 142



9.12 Yarn guide complete


Pos	Designation	Track	ID		Pos	Designation	ID
E6.2					E6.2		
1	FF carriage complete E7-8	1+8	243 939		1a	FF bow 1+8 complete E7-8	212 892
2	FF carriage complete E7-8	2+7	243 938		2a	FF bow 2+7 complete E7-8	212 914
3	FF carriage complete E7-8	3+6	243 937		3a	FF bow 3+6 complete E7-8	212 925
4	FF carriage complete E7-8	4+5	243 936		4a	FF bow 4+5 complete E7-8	212 910
E10 E12 E14 E6.2(E12M.10) E7.2 E8.2 E14/12					E10 E12 E14 E6.2(E12M.10) E7.2 E8.2 E14/12		
1	FF carriage complete E10-14	1+8	243 943		1a	FF bow 1+8 complete E10-14	212 994
2	FF carriage complete E10-14	2+7	243 942		2a	FF bow 2+7 complete E10-14	212 996
3	FF carriage complete E10-14	3+6	243 941		3a	FF bow 3+6 complete E10-14	212 995
4	FF carriage complete E10-14	4+5	243 940		4a	FF bow 4+5 complete E10-14	212 997
E16 E18					E16 E18		
1	FF carriage complete E16-18	1+8	243 947		1a	FF bow 1+8 complete E16-18	223 199
2	FF carriage complete E16-18	2+7	243 946		2a	FF bow 2+7 complete E16-18	223 201
3	FF carriage complete E16-18	3+6	243 945		3a	FF bow 3+6 complete E16-18	223 200
4	FF carriage complete E16-18	4+5	243 944		4a	FF bow 4+5 complete E16-18	223 202
5	Limiter on the left complete		244 099		11	Yarn guide star complete	209 257
6	Limiter on the right complete		244 098		13	Shim	213 035
7	Slider with eyelet		230 709		500	Hexagon screw M5x10	020 351
10	FF carriage complete		243 062				



9.13 Left friction feed wheel


9.13 Left friction feed wheel

Pos	Designation		Id	Pos	Designation		Id
Σ	Friction feed wheel on the left complete		243 571	14	V-ribbed belt pulley		221 268
1	Housing		240 368	15	Ribbed V-belt V3J 406		206 927
2	Friction roller complete		231 704	16	Rod		221 319
3	Three-phase AC motor complete		219 800	18	Cover		230 758
	3a	Microswitch	008 664	19	Knurled screw		223 361
4	Deflector complete 8-fold		250 089	20	Rod		230 658
	4a	Support rail	250 055	21	Grounding plate		256 622
	4b	Eyelet holder complete	250 077	22	Spring plate		256 702
	540	Spring dowel sleeve 4x15	020 783	500	Screw KB30x8		236 228
	541	Hexagon nut M8-8	022 843	501	Screw 20x10		244 736
7	Yarn guide rod complete		239 431	503	Cap screwM5x12		020 132
	570	Eyelet 8	021 504	504	Cap screwM5x16		022 726
8	Stop motion rail on the right complete		230 690	506	Screw KB 40x14		241 358
9	Stop motion rail on the left complete with eyelets		230 683	507	Screw KB 40x25		241 595
	9b	Eyelet	230 662	509	Washer5,3x22x2,5		023 219
	590	Slide bearing	023 627	510	Washer5		020 901
	591	Guide piece	^259 453	512	Shim ring 15x21x1		023 216
11	Bracket		221 316	514	Washer4,3		020 908
12	Cover		251 098	517	Pan-head screwM4x8		023 579
13	Bush		221 391				



9.14 Right friction feed wheel


Pos	Designation		Id	Pos	Designation		Id
Σ	Friction feed wheel on the right complete		243 572	14	V-ribbed belt pulley		221 268
1	Housing		240 368	15	Ribbed V-belt V3J 406		206 927
2	Friction roller complete		231 704	16	Rod		221 319
3	Three-phase AC motor complete		219 800	18	Cover		230 758
	3a	Microswitch	008 664	19	Knurled screw		223 361
4	Deflector complete 8-fold		250 089	20	Rod		230 658
	4a	Support rail	250 055	21	Grounding plate		256 622
	4b	Eyelet holder complete	250 077	22	Spring plate		256 702
	540	Spring dowel sleeve 4x15	020 783	500	Screw KB30x8		236 228
	541	Hexagon nut M8-8	022 843	501	Screw 20x10		244 736
7	Yarn guide rod complete		239 431	503	Cap screw M5x12		020 132
	570	Eyelet 8	021 504	504	Cap screw M5x16		022 726
8	Stop motion rail on the right complete		230 690	506	Screw KB 40x14		241 358
9	Stop motion rail on the right complete with eyelets		230 682	507	Screw KB 40x25		241 595
	9b	Eyelet	230 662	509	Washer5,3x22x2,5		023 219
	590	Slide bearing	023 627	510	Washer5		020 901
	591	Guide piece	259 453	512	Shim ring 15x21x1		023 216
11	Bracket		221 316	514	Washer4,3		020 908
12	Cover		251 098	517	Pan-head screw M4x8		023 579
13	Bush		221 391				



9.14 Right friction feed wheel


Notes:

10 Fluff absorption




10.1 Fluff absorption

Pos	Designation	ID		Pos	Designation	ID
Σ	Fluff absorption			4	Lint container	245 024
1	Suction fan complete	259 004		5	Set of hose complete	255 067
2	Suction hose 29x25x2800	252 627		550	Countersunk head screw M4x12	023 062
3	Cable clip	250 051		551	Cap screw M4x8	022 501



10.1.1 Lint container


Pos	Designation	Id		Pos	Designation	Id
Σ	Lint container			6*	Sealing plug	245 029
1	Lint container	245 024		10*	Cover with filter	251 335
5*	Sealing plug	245 028		501*	Cap screw M6x10	023 690



10.1 Fluff absorption


10.1.2 Set of hose

Pos	Designation		ID		Pos	Designation	ID
Σ	Set of hose complete 530/520C		255 067		4	Connection piece Flent	245 022
1	Angle connection on the right		250 121		500	Suction hose 20x16x400	244 983
2	Angle connection on the left		251 101		501	Suction hose 20x16x40	251 043
3	T-piece FLENT		245 021		502	Suction hose 20x16x570	255 085
	530	O-ring 15x1,5	250 054		504*	Countersunk head screw M4x12	023 062
	531*	Cap screwM4x8	022 501		506*	Cable clip	250 051




10.1.3 Suction tube

Pos	Designation	ID		Pos	Designation	ID
Σ	Suction tube complete E5-14 E10 E12 E14 E6.2 E7.2 E6.2(12m.10) E14/12	251 310		Σ	Suction tube complete E16-18 E16 E18 E8.2	251 311
1	Suction tube	255 386		1	Suction tube	255 605
2	Bracket	255 627		2	Bracket	255 627
500	Screw KB30x6	241 424		500	Screw KB30x6	241 424



Notes:


11 Operation and control



11.1 Input unit


11.1 Input unit

Pos	Designation	Id		Pos	Designation	Id
Σ	Input unit complete	240 194				
1	Base frame	240 195		10*	Touch panel spare parts package	244 554
3	Bearing strip complete	240 198		502	Washer	020 901
4	Display touch complete	250 298		503	Screw KB 50x12	240 359
6	Touch pen	242 812		507	Screw KB 50x15	251 728



11.2 Starting device


Pos	Designation	Id	Pos	Designation	Id
Σ	Starting device complete	240 306	12	Sliding nut (slot nut)	225 099
1	Engaging rod	240 227	502	Screw M6x25	023 510
2	Bearing on the left complete	250 071	503	Cap screwM6x16	020 135
3	Guide rail at the bottom complete	257 309	504	Pan-head screwM5x14	023 588
6*	Cover plate on the right	250 931	506	Cap screwM6x12	020 134
7*	Cover plate on the left	250 932	507	Cap screwM6x20	020 136
8	Bearing on the right complete	252 964	508	Washer	020 872
9	Switch with cable to safety doors	223 350	511	Adhesive base	243 055
11	Locating bolt	219 107	512	Cap screwM6x10	023 690



11.2 Starting device


11.2.1 Bearing of the engaging rod

Pos	Designation	ID	Pos	Designation	ID
L	Bearing on the left complete	250 071			
1	Bearing on the left	245 218	505	Hexagon nut M8-6	020 838
1a	Clip bearing MCM 12-04	023 639	506	Dowel pin 1,5x8	236 923
2	Support of buffer	220 561	507	Spring dowel sleeve 6x20	023 719
2a	O-ring 14x4	023 237	508	Shoulder screw M4x24,8x7,7	240 299
3	Shaft on the left	245 219	509	Shoulder screw	251 316
4	Rotor	253 776	510	Shim ring 12x18x1	023 315
5	Switch flag	245 220	511	Locking ring12x1	020 951
6	Spring mandrel	251 340	512	Compression spring 1,25x15x98,2	023 609
7	Disk	245 222	513	Compression spring 0,5x11x12	251 369
8	Shoulder screw	254 528			
9	Distance bolt	240 287	R	Bearing on the right complete	252 964
500	Cap screw M4x6	023 067	1	Bearing on the right	240 230
501	Cap screwM4x8	022 501	1a	Clip bearing MCM 12-04	023 639
502	Shim ring 4x8x1	023 369	2	Shaft on the right	242 888
503	Card engaging	259 000	500	Shim ring 12x18x1	023 315
504	Adhesive magnet direct current	026 233	502	Locking ring12x1	020 951




11.3 Collecting area - control

Pos	Designation	Id		Pos	Designation	Id
Σ	Reflector complete	256 826		Σ	Light barrier complete	256 825
1	Mounting plate reflector	256 675		1	Holding angle light barrier	256 674
500	Blind rivet A3x8-Al	023 158		500	Cap screwM3x10	022 991
501	Reflector 20x20 mm	243 356		501	Light barrier W100-P4330	243 355
900*	Cap screwM6x12	020 134		900*	Cap screwM6x12	020 134
				901*	Washer6	020 872




11.4 Signal light

Pos	Designation		Id		Pos	Designation		Id
Σ	Signal light LED		240 395					
	500	Pan-head screwM4x14	023 037					
	501	Serrated lock washer A4,3-FS	022 482					




11.5 Shock stop motion
E10 | E12 | E14 | E6.2 | E7.2 | E6.2(12m.10) | E14/12

Pos	Designation	ID		Pos	Designation	ID
Σ	Shock stop motion complete E3	241 819				
1	Shock stop motion (Piezo)	220 011		10*	Cable piezo NB OKC	240 518
2	Connecting cable piezo sensor	220 061		500*	Pan-head screw M4x8	023 036
3	End plug piezo sensor	220 053		502*	Cable clipN-3B, 5 mm	210 729




11.6 Shock stop motion E16 | E18 | E8.2

Pos	Designation	Id		Pos	Designation	Id
Σ	Shock stop motion complete E3	250 384		4	Cable connection piezo	250 295
1	Shock stop motion (Piezo)	220 011		10*	Cable piezo	240 518
2	Cable connection piezo	250 291		500*	Pan-head screwM4x8	023 036
3	End plug piezo sensor	220 053		502*	Cable clip N-3B, 5 mm	210 729




11.7 Measuring device

Pos	Designation	ID		Pos	Designation	ID
Σ	Measuring device			6	Impulse sensor GLM complete	257 003
1	Measuring bar	257 370		501	Washer	020 881
2	Guide	251 676		502	Pan-head screw	241 603
3	Stop point	209 289		503	Screw 60x20	243 625
4	Guide	240 672		530	Setscrew	230 803
5	Guide exterior	251 605		10*	Bearing fork	240 689



Notes:


12 Protective units



12.1 Lateral safety doors


12.1 Lateral safety doors

Pos	Designation	Id		Pos	Designation	Id
Σ	Safety door on the left			Σ	Safety door on the right	
1	Safety door on the left	250 562		1	Safety door on the right	250 563
2	Hinge	241 994		2	Hinge	241 994
3	Plate	224 717		3	Plate	224 717
4	Locking plate	219 748		4	Locking plate	219 748
16	ActuatorAZ 15/16	255 492		16	ActuatorAZ 15/16	255 492
505	Screw KB 60x30	237 683		505	Screw KB 60x30	237 683
506	Screw KB 40x14	241 358		506	Screw KB 40x14	241 358
510	Screw KB 60x20	237 682		510	Screw KB 60x20	237 682




12.2 Panelling

Pos	Designation	Id	Pos	Designation	Id
1	Cover 1 completeCover completeCover completeCover complete	257 303	3	Cover 3 completeCover completeCover completeCover complete	257 305
	1a Cover 1	257 296		3a Cover 3	257 298
	1b Inlet type handle	251 376		1b Inlet type handle	251 376
	1c Stripper	219 393		1c Stripper	219 393
	1d Magnet	204 666		1d Magnet	204 666
2	Cover 2 completeCover completeCover completeCover complete	257 304	4	Cover 4 completeCover completeCover completeCover complete	257 306
	2a Cover 2	257 297		4a Cover 4	257 299
	1b Inlet type handle	251 376		1b Inlet type handle	251 376
	1c Stripper	219 393		1c Stripper	219 393
	1d Magnet	204 666		1d Magnet	204 666
5	Control unit panelling on the left complete	251 233	6	Control unit panelling on the right complete	251 234
	5a Control unit panelling on the left	251 185		6a Control unit panelling on the right	251 186
	5b Side part	244 989		6b Side part	244 989
	5c Hinge	250 273		6c Hinge	250 273
	5d Bracket	240 412		6d Bracket	240 412
	550 Screw KB 50x12	240 359		550 Screw KB 50x12	240 359
	551 Cap screwM6x16	020 135		551 Cap screwM6x16	020 135




12.3 Rear panel

Pos	Designation	Id		Pos	Designation	Id
1	Panelling at the rear complete	257 668		1a	Panelling	257 662
				1b	Safety sash fastener	243 052




13 Electrical equipment



13.1 Fuses


13.1 Fuses

	Designation	Id
	Fuse 1,0A F 5x20	008 748
	Fuse 3,15A T/440V 6,3x32	025 261
	Fuse 10A T/440V 6,3x32Fuse	025 258
	Fuse 2,5A T/440V 6,3x32	217 465
	Fuse 1,6A T/440V 6,3x32	236 229
	Fuse 6,3A T/440V 6,3x32	026 809
	Fuse 8A T/440V 6,3x32Fuse	241 866
	Fuse 12,5A T/440V 6,3x32	232 367




13.2 Circuit diagram (222) as PDF

Designation	ID	Marking
Circuit diagram 222 German	257 280	_DE
Circuit diagram 222 English	257 280	_GB
Circuit diagram 222 Chinese	257 280	_CN

You will find the circuit diagram 222 on the CMS documentation DVD with the ID no. 257 157



13.3 Trailing cable



Designation		ID	Designation		ID
Σ	Trailing cable set 530 2IMP-2	259 303			
	Cable carriage at the rear XR332	253 549		Cable impulse sensor 2 at the rear XR136_520/530 OKC3	259 357
					
	Cable carriage at the front XR333	253 550		Cable impulse sensor 2 at the front XR137_520/530 OKC3	259 358
					
	Cable yarn carrier XR161	254 886			
					

13.4 Cable set installation




Designation		Id	Designation		Id	
Σ	Cable set installation 5XX OKC	253 618				
1	Loom of cables base 1 5XX	253 619		3	Loom of cables 5XX OKC	253 621
2	Loom of cables base 2OKC	240 257		4	Loom of cables comb OKC	240 259
6	Cable switch main take-down 50" ECO2	252 541		7	Cable supply FKE lamp ECO2	252 587
						

13.4 Cable set installation

13.4.1 Cable set base 1



Designation		Id	Designation		Id
Σ	Loom of cables base 1 5XX	253 619			
	Cable engaging ECO2	252 538		Cable protective device on the left 5XX	253 620
					
	Cable feed wheel on the left 50" OKC	240 464			
					

13.4.2 Loom of cables base 2






Designation		Id	Designation		Id		
Σ	Loom of cables base 2	240 257					
	Cable motor HAAB OKC	240 291		Cable resolver drive OKC 3XX	240 296		
							
	Cable racking limit switch OKC 3XX	240 292		Cable racking motor OKC 3XX	240 297		
							
	Cable fan drive 3XX OKC	240 293		Cable resolver racking OKC 3XX	240 298		
							
	Cable feed wheel on the right OKC 3XX	240 294		Cable protective device on the right OKC	253 441		
							
	Cable drive motor OKC 3XX	240 295					
							

13.4 Cable set installation

13.4.3 Loom of cables comb


Designation		Id	Designation		Id
Σ	Loom of cables comb OKC	240 259			
	Cable motor comb hookOKC	240 308		Cable switch combOKC	240 311
					
	Cable switch KAHA OKC	240 309		Cable switch HAAB OKC	240 312
					
	Cable motor combOKC	240 310			
					

13.4.4 Loom of cables 5XX

Designation		Id	Designation		Id
Σ	Loom of cables 5XX OKC	253 621			
	Cable motor auxiliary take-down 50" okc	240 467		Cable power supply unit of mains supply OKC	240 505
					
	Cable impulse sensor auxiliary take-down 50" OKC	240 468		Cable power supply lighting	236 572
					
	Cable power supply WAZ/F 50" OKC	240 469		Cable switch auxiliary take-down 3xx OKC	240 472
					
	Cable power supply servo 50" OKC	240 502		Cable power supply FLENT 50" OKC	251 231
					


Notes:

14 Control electronics



14.1 Control cabinet

Pos	Designation	ID		Pos	Designation	ID
Σ	Control unit complete 530	254 850		6	Card BIO ECO2	301 007
1	Control unit without equipment 5XX ECO2	254 854		7	Card final stages 4SM 7TE	300 943
2	Power supply unit CG54	300 923		8	Card N-CPU 432	300 965
3	Battery plug-in unit	301 008		9	Card Power CPU B	301 009
4	Card Servo 6	301 000		10	Card IPC P8XS 01	257 040
5	Card C-WAZ ECO2	301 006		521*	Axial flow fan Servo 5	229 059



15 Deliverable accessories




You can order the following tools, lubricants and expendables.
The following list does not correspond to the scope of delivery of the knitting machine.

15.1 Tool

15.1 Tool

Pos	Designation	Id	Pos	Designation	Id
1	Channel support E4	062 309	6	Groove file 1,33mm E3-4	006 169
	Channel support E5, E2,5.2	062 310		Groove file 1,25mm E5-8, E3,5.2	006 170
	Channel support E7, E3,5.2	062 312		Groove file 0,90mm E10-12, E5.2 6.2	006 175
	Channel support E8	062 313		Groove file 0,73mm E14, E7.2	006 173
	Channel support E10, E5.2	062 314		Groove file 0,45mm E16-18, E9.2	006 179
	Channel support E12, E6.2	062 315	7	Key of switch cabinet	009 346
	Channel support E14, E7.2	218 069	8	Groove cleaner E4	031 232
	Channel support E16, E8.2	230 188		Groove cleaner E5	031 233
	Channel support E18, E9.2	230 189		Groove cleaner E6	031 234
	Channel support E20	230 190		Groove cleaner E7, E3,5.2	031 235
2	Channel chisel E14-20 (E5-14)	062 316		Groove cleaner E8	031 236
	Channel chisel E4-8 (E3,5.2)	062 317		Groove cleaner E10 (E5.2)	031 238
	Channel chisel E10-14	062 318		Groove cleaner E12 (E6.2)	031 240
3	Yarn guide on the left	227 071		Groove cleaner E14 (E7.2)	031 242
	Yarn guide on the right	227 070		Groove cleaner E16	225 111
4	Working hook	227 249		Groove cleaner E18 (E9.2)	225 112
5	Extraction hook	232 027		Groove cleaner E20	225 113
	5a Small pin	202 843	9	Measuring tape L=150cm	228 180
	5b Pencil	232 022	10	Tool kit	209 527



15.2 Lubricating stuff


Pos	Designation	Id		Pos	Designation	Id
1	Textile machines oil T46, 1l	230 614		4	Oil combifix	216 732
2	Grease OKS 475, 1kgGrease	009 200		5	White grease paste OKS270	229 372
3	Grease OKS 475, 150gGrease	005 351		6	Grease Staburags NBU 12/300KP	231 191



15.3 Mechanical parts

15.3 Mechanical parts

Pos	Designation	Id		Pos	Designation	Id
1	Cap screw M4x8	020 091		11	Cut cable 203x3,6mm	025 815
2	Countersunk screw M3x6	020 286			Cut cable T50L	026 294
3	Cap screw M5x16	022 726			Cut cable 140x3,6mm	008 379
4	Cap screw M6x14	022 658			Cut cable 302x4,8mm	008 642
5	Setscrew M16x50	023 235			Cut cable 92x2,4mm	008 378
6	Dowel pin 3x7	020 643		12	Reusable tie ABV 232 320mm	026 557
7	Dowel pin 3x10	020 645				
8	Dowel pin 3x12	020 647				
9	Dowel pin 5x12	021 988				
10	Dowel pin 5x18	022 622				




16 Special attachments



16.1 Yarn carrier type 2, E10 | 12 | E14 | E7.2 | E8.2 | E9.2


16.1 Yarn carrier type 2, E10 | 12 | E14 | E7.2 | E8.2 | E9.2

Track	Pos	Designation	ID		Track	Track		ID
1+8	FF carriage 1+8 complete EW 23		259 122		3+6	FF carriage 3+6 complete EW 23		258 630
	1	FF carriage EW 23	258 326			1	FF carriage EW 23	258 326
	2	FF bow 1+8 complete E10-14	259 929			2	FF bow 3+6 complete E10-14	258 613
	FF carriage 1+8 complete EW 29		259 123			FF carriage 3+6 complete EW 29		259 127
	1	FF carriage EW 29	259 034			1	FF carriage EW 29	259 034
	2	FF bow 1+8 complete E10-14	259 929			2	FF bow 3+6 complete E10-14	258 613
	FF carriage 1+8 complete EW 43		259 924			FF carriage 3+6 complete EW 43		259 926
	1	FF carriage EW 43	259 923			1	FF carriage EW 43	259 923
	2	FF bow 1+8 complete E10-14	259 929			2	FF bow 3+6 complete E10-14	258 613
	FF carriage 1+8 complete EW 46		259 124			FF carriage 3+6 complete EW 46		259 128
	1	FF carriage EW 46	258 912			1	FF carriage EW 46	258 912
	2	FF bow 1+8 complete E10-14	259 929			2	FF bow 3+6 complete E10-14	258 613
2+7	FF carriage 2+7 complete EW 23		258 629		4+5	FF carriage 4+5 complete EW 23		258 631
	1	FF carriage EW 23	258 326			1	FF carriage EW 23	258 326
	2	FF bow 2+7 complete E10-14	258 611			2	FF bow 4+5 complete E10-14	258 615
	FF carriage 2+7 complete EW 29		259 125			FF carriage 4+5 complete EW 29		259 129
	1	FF carriage EW 29	259 034			1	FF carriage EW 29	259 034
	2	FF bow 2+7 complete E10-14	258 611			2	FF bow 4+5 complete E10-14	258 615
	FF carriage 2+7 complete EW 43		259 925			FF carriage 4+5 complete EW 43		259 927
	1	FF carriage EW 43	259 923			1	FF carriage EW 43	259 923
	2	FF bow 2+7 complete E10-14	258 611			2	FF bow 4+5 complete E10-14	258 615
	FF carriage 2+7 complete EW 46		259 126			FF carriage 4+5 complete EW 46		259 130
	1	FF carriage EW 46	258 912			1	FF carriage EW 46	258 912
	2	FF bow 2+7 complete E10-14	258 611			2	FF bow 4+5 complete E10-14	258 615



16.2 Yarn carrier type 2, E16 | E18


Track	Pos	Designation	ID		Track	Track		ID
1+8		FF carriage 1+8 complete EW 23 E16-18	260 047		3+6		FF carriage 3+6 complete EW 23 E16-18	260 049
	1	FF carriage EW 23	258 326			1	FF carriage EW 23	258 326
	2	FF bow 1+8 complete E16-18	259 944			2	FF bow 3+6 complete E16-18	259 946
		FF carriage 1+8 complete EW 29 E16-18	260 051				FF carriage 3+6 complete EW 29 E16-18	260 053
	1	FF carriage EW 29	259 034			1	FF carriage EW 29	259 034
	2	FF bow 1+8 complete E16-18	259 944			2	FF bow 3+6 complete E16-18	259 946
		FF carriage 1+8 complete EW 43 E16-18	260 055				FF carriage 3+6 complete EW 43 E16-18	260 057
	1	FF carriage EW 43	259 923			1	FF carriage EW 43	259 923
	2	FF bow 1+8 complete E16-18	259 944			2	FF bow 3+6 complete E16-18	259 946
		FF carriage 1+8 complete EW 46 E16-18	260 016				FF carriage 3+6 complete EW 46 E16-18	260 018
	1	FF carriage EW 46	258 912			1	FF carriage EW 46	258 912
	2	FF bow 1+8 complete E16-18	259 944			2	FF bow 3+6 complete E16-18	259 946
2+7		FF carriage 2+7 complete EW 23 E16-18	260 048		4+5		FF carriage 4+5 complete EW 23 E16-18	260 050
	1	FF carriage EW 23	258 326			1	FF carriage EW 23	258 326
	2	FF bow 2+7 complete E16-18	259 945			2	FF bow 4+5 complete E16-18	259 947
		FF carriage 2+7 complete EW 29 E16-18	260 052				FF carriage 4+5 complete EW 29 E16-18	260 054
	1	FF carriage EW 29	259 034			1	FF carriage EW 29	259 034
	2	FF bow 2+7 complete E16-18	259 945			2	FF bow 4+5 complete E16-18	259 947
		FF carriage 2+7 complete EW 43 E16-18	260 056				FF carriage 4+5 complete EW 43 E16-18	260 058
	1	FF carriage EW 43	259 923			1	FF carriage EW 43	259 923
	2	FF bow 2+7 complete E16-18	259 945			2	FF bow 4+5 complete E16-18	259 947
		FF carriage 2+7 complete EW 46 E16-18	260 017				FF carriage 4+5 complete EW 46 E16-18	260 019
	1	FF carriage EW 46	258 912			1	FF carriage EW 46	258 912
	2	FF bow 2+7 complete E16-18	259 945			2	FF bow 4+5 complete E16-18	259 947



16.3 Complete intarsia yarn carriers type 2


16.3 Complete intarsia yarn carriers type 2

Designation	Gauge	Track	Pos	Id		Designation	Gauge	Track	Pos	Id
IFF carriage complete	E6.2	1 8	1	259 736		IFF carriage complete	E16 E18	1 8	1	259 744
		2 7	2	259 737				2 7	2	259 745
		3 6	3	259 738				3 6	3	259 746
		4 5	4	259 739				4 5	4	259 747
	E10 E12 E14 E7.2 E8.2	1 8	1	259 740						
		2 7	2	259 741						
		3 6	3	259 742						
		4 5	4	259 743						



16.4 Plating yarn carrier 3+6


Pos	Designation	Id		Pos	Designation	Id
Σ	Plating yarn carrier carriage 3+6 complete					
	E6.2	252 784		7	Eyelet holder complete	252 825
	E10 E12 E14 E7.2 E8.2 E6.2(12m.10) E12/14	252 786		8	Eyelet holder complete	252 824
	E16 E18	252 788		9	Distance bushing	252 796
1	Plating yarn carrier carriage	252 806		10	Shim	213 035
2	Sliding piece	212 583		11	Shim	216 143
3	Slider	252 798		12	Adjusting screw	253 436
4	Plating yarn carrier bow 3+6			500	Hexagon screw M4x5	243 779
	E6.2	252 821		501	Hexagon screw M4x10	020 346
	E10 E12 E14 E7.2 E8.2 E6.2(12m.10) E12/14	252 822		502	Hexagon screw	252 832
	E16 E18	252 823		503	Setscrew M4x16	254 196
5	Plating yarn carrier bow 3+6 E6.2	252 800		504	Compression spring	021 399
	Plating yarn carrier bow 3+6 E10-E18	252 808		505	Threaded bolt	213 399
6	Sliding piece	252 797		506	Compression spring	253 058



16.5 Plating yarn carrier 4+5


16.5 Plating yarn carrier 4+5

Pos	Designation	Id	Pos	Designation	Id
Σ	Plating yarn carrier carriage 4+5 complete				
	E6.2	252 783	7	Eyelet holder complete	252 815
	E10 E12 E14 E7.2 E8.2 E6.2(12m.10) E14/12	252 785	8	Eyelet holder complete	252 816
	E16 E18	252 787	9	Distance bushing	252 796
1	Plating yarn carrier carriage	252 806	10	Shim	213 035
2	Sliding piece	212 583	11	Shim	216 143
3	Slider	252 798	12	Adjusting screw	253 436
4	Plating yarn carrier bow 3+6		500	Hexagon screw M4x5	243 779
	E6.2	252 791	501	Hexagon screw M4x10	020 346
	E10 E12 E14 E7.2 E8.2 E6.2(12m.10) E14/12	252 792	502	Hexagon screw	252 832
	E16 E18	252 793	503	Setscrew M4x16	254 196
5	Plating yarn carrier bow 3+6 E6.2	252 799	504	Compression spring	021 399
	Plating yarn carrier bow 3+6 E10-E18	252 807	505	Threaded bolt	213 399
6	Sliding piece	252 797	506	Compression spring	253 058



16.6 Carriage of plating yarn carrier EW43 | EW46


Pos	Designation	Id		Pos	Designation	Id
A	Plating FF carriage complete EW 43	257 241		B	Plating FF carriage complete E5-18	244 998
1	FF carriage EW 43	257 240		1	FF carriage EW 46	244 253
2	Sliding piece	212 583		1a	FF carriage	243 881
3	Shim	216 143		1b	Sliding piece	212 583
4	Threaded bolt	213 399		1c	Shim	216 143
500	Compression spring4,0x0,55x11	021 399		1d	Threaded bolt	213 399
10*	Shim	213 035		500	Compression spring4,0x0,55x11	021 399
510*	Hexagon screw M5x10	020 351		2	Shim	213 035
				510	Hexagon screw M5x10	020 351



16.7 Carriage of plating yarn carrier (adjustable)


16.7 Carriage of plating yarn carrier (adjustable)

Pos	Designation	Id		Pos	Designation	Id
Σ	Plating yarn carrier carriage complete	251 867				
1	Carriage of yarn carrier	251 864		7	Guide part	253 226
2	Sliding piece	212 583		8	Shim	213 035
3	Shim	216 143		500	Compression spring	021 399
4	Threaded bolt	213 399		511	Washer ⁴	022 481
5	Insert on the right	251 866		512	Hexagon screw M4x8	022 461
6	Insert on the left	251 865		513	Hexagon screw M5x10	020 351



16.8 Yarn length measuring device on the left complete


Pos	Designation	Id		Pos	Designation	Id
Σ	Yarn length measuring device on the left complete	257 600				
1	Yarn length measuring device on the left complete	257 283		10	Operating instructions of ASCON assembly	259 381
2	Cable ASCON	257 239		500	T-head bolt M8x25	022 866
3	Support on the left	257 122		501	Serrated nut M8-10	023 026
4	Connecting lug on the left	257 137		502	Cap screw M4x8	022 501
5	Adjustment weight	212 241		503	Cable tape 302x4,8	008 642
8	DVD with operating instructions	258 391		504	Cap screw M5x12	020 132
9	Holding plate	258 386		505	Washer5	020 871



16.8 Yarn length measuring device on the left complete


16.8.1 Yarn length measuring device

Pos	Designation	Id		Pos	Designation	Id
Σ	Yarn length measuring device on the left complete	257 283		8	Yarn guide rod	257 139
1	Housing	257 281		9	Card Ascon	255 000
2	Support	257 278		10	Threaded strip	257 138
3	Cover	257 273		500	Pan-head screw M5x10	023 247
4	Fan with plug	257 048		501	Screw 50x15	251 728
5	Protective grid fan Servo5	229 142		502	Sheet metal screw ST3,5x13	022 940
6	Sensor	211 354		503	Oval head screw with washer M3x10	023 380
6a	Rubber running ring	258 582		504	Spring nut M5	022 873
7	Sensor complete	212 406		505	Serrated lock washer J3,7	022 554



16.9 Yarn length measuring device on the right complete


Pos	Designation	Id		Pos	Designation	Id
Σ	Yarn length measuring device on the right complete	257 599				
1	Yarn length measuring device on the right complete	257 282		6	Operating instructions of ASCON assembly	259 381
2	Cable ASCON	257 239		500	T-head bolt M8x25	022 866
3	Support right	257 121		501	Serrated nut M8-10	023 026
4	Connecting lug on the right	257 136		502	Cap screwM4x8	022 501
5	Adjustment weight	212 241		503	Cable tape 302x4,8	008 642
8	DVD with operating instructions	258 391		504	Cap screwM5x12	020 132
9	Holding plate	258 386		505	Washer5	020 871



16.9 Yarn length measuring device on the right complete


16.9.1 Yarn length measuring device on the right

Pos	Designation	Id		Pos	Designation	Id
Σ	Yarn length measuring device on the right complete	257 282		8	Yarn guide rod	257 139
1	Housing	257 281		9	Card Ascon	255 000
2	Support	257 278		10	Threaded strip	257 138
3	Cover	257 273		500	Pan-head screw M5x10	023 247
4	Fan with plug	257 048		501	Screw 50x15	251 728
5	Protective grid fan Servo5	229 142		502	Sheet metal screw ST3,5x13	022 940
6	Sensor	211 354		503	Oval head screw with washer M3x10	023 380
6a	Rubber running ring	258 582		504	Spring nut M5	022 873
7	Sensor complete	212 406		505	Serrated lock washer J3,7	022 554



16.10 Storage feed wheel MSF 2


Pos	Designation	ID	Note
Σ	Attachment set storage feed wheel MSF-2	259 575	Please order the MSF-2 spare parts at: MEMMINGER-IRO GMBH Jakob-Mutz-Strasse 7 D-72280 Dornstetten Tel.: +49 (0)7443 281-0 Fax: +49 (0)7443 281-101 The item no. and the designation for the MSF-2 spare parts can be found in the enclosed assembling instructions of the company MEMMINGER-IRO.
1	Transformer MSF-2 with cable	259 611	
2	Mounted set MSF-2 without transformer	259 612	
5*	Storage feed wheelMSF-2	259 604	



16.11 Bobbin holder on the left


16.11 Bobbin holder on the left

Pos	Designation	ID		Pos	Designation	ID
Σ	Bobbin holder on the left	253 965		501	Pan-head screwM4x25	023 511
1	Support	253 969		502	Washer4	022 481
2	Support	252 769		503	Hexagon nut M4-6	022 536
3	Leaf spring	253 350		505	Washer6	022 431
4	Support on the left	253 347		506	Hexagon nut M6-6	022 899
5	Spacer	253 349		507	Pan-head screwM4x16	023 412
6	Yarn detector Massardi	226 964		508	Pan-head screw M4x12	023 062
7	Clamp	228 583		509	Pan-head screwM8x16	023 113
8	Slot nut	228 851		510	Pan-head screwM8x18	251 331
10	Cover	253 968		511	Pan-head screwM6x30	023 451
11	Holding angle	253 964		512	Serrated lock washer A4,3	022 482
12	Holding angle	253 963		513	Pan-head screwM4x6	022 946
13	Holding angle	253 967		514	Pan-head screwM4x10	023 450
14	Cable plating	253 468		515	Cap nut M4-6	253 805




16.12 Bobbin holder on the right

Pos	Designation	ID	Pos	Designation	ID
Σ	Bobbin holder on the right	253 966	501	Pan-head screwM4x25	023 511
1	Support	253 969	502	Washer4	022 481
2	Support	252 769	503	Hexagon nut M4-6	022 536
3	Leaf spring	253 350	505	Washer6	022 431
4	Support right	253 348	506	Hexagon nut M6-6	022 899
5	Spacer	253 349	507	Pan-head screwM4x16	023 412
6	Yarn detector Massardi	226 964	508	Pan-head screw M4x12	023 062
7	Clamp	228 583	509	Pan-head screwM8x16	023 113
8	Slot nut	228 851	510	Pan-head screwM8x18	251 331
10	Cover	253 968	511	Pan-head screwM6x30	023 451
11	Holding angle	253 964	512	Serrated lock washer A4,3	022 482
12	Holding angle	253 963	513	Pan-head screwM4x6	022 946
13	Holding angle	253 967	514	Pan-head screwM4x10	023 450
14	Cable plating	253 468	515	Cap nut M4-6	253 805




16.13 Additional bobbin board

Pos	Designation	Id		Pos	Designation	Id
Σ	Additional bobbin board	241 852				
1	Additional bobbin board welded	241 851		4	DiskD=130	062 385
2	Positioning pin	202 777		500	Pan-head screw M4x30	023 681
3	Bobbin support	200 363		501	Washer5,3x30x1,25	023 556



16.14 Sanding Paper Brake

Pos	Designation		ID		Pos	Designation		ID
Σ	Conversion kit sanding paper brake		257 674					
1	Shaft complete		257 509		2	Wave		241 318
	1a	Wave	241 318		3	Support sanding paper brake		257 586
	1b	Adjusting part	257 508		4	Support sanding paper brake on the left		257 626
	510	Compression spring0,32x2,51x14,20	237444		500	Screw KB 60x20		237 682
	511	SetscrewM4x6	022 955		501	SetscrewM4x5		023 088




16.14 Sanding Paper Brake

Notes:

17 Conversion kit with 24 and 32 IFF Type 2

	Designation	ID
24 IFF:	Conversion kit 24 IFF Type 2 E10 E12 E14	257 442
	Conversion kit 24 IFF Type 2 E16 E18	257 443
	Conversion kit 24 IFF Type 2 E6.2	257 445
	Conversion kit 24 IFF Typ2 E7.2 E6.2(12m.10) E14/12	257 449
	Conversion kit 24 IFF Type 2 E8.2	257 450
32 IFF:	Conversion kit 32 IFF Typ2 E10 E12 E14	257 381
	Conversion kit 32 IFF Type2 E16 E18	257 382
	Conversion kit 32 IFF Type 2 E6.2	257 441
	Conversion kit 32 IFF Typ2 E7.2 E6.2(12m.10) E14/12	256 990
	Conversion kit 32 IFF Typ2 E8.2	257 178




17.1 Overview of conversion kit with 24 IFF E10 | E12 | E14 | E16 | E18 | E8.2

17.1 Overview of conversion kit with 24 IFF E10
| E12 | E14 | E16 | E18 | E8.2


Pos	Designation	Id		Pos	Designation	Id
Σ	Conversion kit 24 IFF Type 2			22	Clamping and cutting bed on the right E10-14	253 681
	E10 E12 E14	257 442			Clamping and cutting bed on the right E16-18 E8.2	253 683
	E16 E18	257 443		24	Stopping device 16-fold	259 455
	E8.2	257 450		25	DVD instructions conversion kit IFF	245 169
1	Magnetic holder complete	229 373		26	Adjusting part for yarn carrier bow	250 119
2	Additional bobbin board 50" IFF complete	244 424		27	Yarn guide complete E10-14 IFF 24(E8.2)	256 936
3	Yarn tensioner on the left completeE10-18	258 461			Yarn guide complete E16-18 IFF 24	256 937
4	Yarn tensioner on the right complete E10-18	258 463		28	Ceramic eyelet	240 640
5	Yarn guide bar50"	240 324		30	Stitch cam on the left short tuckE10-14+7.2	255 428
6	Support on the left	243 602			Stitch cam on the left short tuckE16-18+8.2	255 547
7	Support on the right	243 603		31	Stitch cam on the right short tuckE10-14+7.2	255 429
8	Support	239 295			Stitch cam on the right short tuckE16-18+8.2	255 548
9	Yarn brake complete	244 347		32	Pressure part short tuck	255 430
10	Clamping bow	244 409		34	Raising cam plate	256 491
11	Yarn control device	237 124		500	Self-locking screw M6x12	023 415
12	Yarn guide bracket complete	241 581		501	Serrated nut M6-10	023 414
15	Friction feed wheel 16 fold on the left complete	244 991		502	Square nut M8	023 269
16	Friction feed wheel 16 fold on the right complete	244 992		503	Pan-head screw M8x16	023 113
19	Deflector on the left complete	259 573		506	Dowel pin 6x16	020 677
20	Deflector on the right complete	259 570		507	Screw M6x20	244 824
21	Left clamping and cutting bed E10-14	253 682		508	Screw KB60x20	237 682
	Left clamping and cutting bed E16-18 E8.2	253 684		510	Pan-head screw M5x10	023 247

17.1 Overview of conversion kit with 24 IFF E10 | E12 | E14 | E16 | E18 | E8.2




17.2 Overview of conversion kit with 24 IFF E6.2

Pos	Designation	Id		Pos	Designation	Id
Σ	Conversion kit 24 IFF Type 2					
	E6.2	257 445		20	Deflector on the right complete	259 570
1	Magnetic holder complete	229 373		21	Left clamping and cutting bed E10-14	253 682
2	Additional bobbin board 50" IFF complete	244 424		22	Clamping and cutting bed on the right E10-14	253 681
3	Yarn tensioner on the left completeE7-8	244 499		25	DVD instructions conversion kit IFF	245 169
4	Yarn tensioner on the right complete E7-8	244 502		26	Adjusting part for yarn carrier bow	250 119
5	Yarn brake complete	244 347		27	Yarn guide complete E7-8 IFF 24	256 935
6	Clamping bow	244 409		30	Stitch cam on the left short tuckE6.2	255 551
7	Ceramic eyelet	240 640		31	Stitch cam on the right short tuckE6.2	255 552
11	Yarn control device	237 124		32	Pressure part short tuck E6.2	255 430
12	Yarn guide bracket complete	241 581		34	Raising cam plate	256 491
15	Friction feed wheel 16 fold on the left complete	244 991		506	Dowel pin 6x16	020 677
16	Friction feed wheel 16 fold on the right complete	244 992		507	Screw M6x20	244 824
19	Deflector on the left complete	259 573		508	Screw KB60x20	237 682



17.3 Overview of conversion kit with 24 IFF
E7.2 | E6.2(12m.10) | E14/12


Pos	Designation	Id		Pos	Designation	Id
Σ	Conversion kit 24 IFF Type 2					
	E7.2 E6.2(12m.10) E14/12	257 449		24	Stopping device 16-fold complete	259 455
1	Magnetic holder complete	229 373		25	DVD instructions conversion kit IFF	245 169
2	Additional bobbin board 50" IFF complete	244 424		26	Adjusting part for yarn carrier bow	250 119
3	Yarn tensioner on the left completeE10-18	258 461		27	Yarn guide complete E10-14 IFF 24	256 936
4	Yarn tensioner on the right complete E10-18	258 463		28	Ceramic eyelet	240 640
11	Yarn control device	237 124		30	Stitch cam on the left short tuckE10-14+7.2	255 428
12	Yarn guide bracket complete	241 581		31	Stitch cam on the right short tuckE10-14+7.2	255 429
15	Friction feed wheel 16 fold on the left complete	244 991		32	Pressure part short tuck	255 430
16	Friction feed wheel 16 fold on the right complete	244 992		34	Raising cam plate	256 491
19	Deflector on the left complete	259 573		506	Dowel pin 6x16	020 677
20	Deflector on the right complete	259 570		507	Screw M6x20	244 824
21	Left clamping and cutting bed E10-14	253 682		508	Screw KB60x20	237 682
22	Clamping and cutting bed on the right E10-14	253 681		510	Pan-head screw M5x10	023 247



17.4 Overview of conversion kit with 32 IFF E10
| E12 | E14 | E16 | E18 | E8.2


Pos	Designation	ID		Pos	Designation	ID
Σ	Conversion kit 32 IFF Type 2			22	Clamping and cutting bed on the right E16-18 E8.2	253 683
	E10 E12 E14	257 381		24	Stopping device 16-fold complete	259 455
	E16 E18	257 382		25	DVD instructions conversion kit IFF	245 169
	E8.2	257 178		26	Adjusting part for yarn carrier bow	250 119
1	Magnetic holder complete	229 373		27	Yarn guide complete IFF E10-14 E8.2	245 163
2	Additional bobbin board 50" IFF complete	244 424			Yarn guide complete IFF E16-18	245 164
3	Yarn tensioner on the left completeE10-18	258 461		28	Ceramic eyelet	240 640
4	Yarn tensioner on the right complete E10-18	258 463		30	Stitch cam on the left short tuckE10-14+7.2	255 428
5	Yarn guide bar50"	240 324			Stitch cam on the left short tuckE16-18+8.2	255 547
6	Support on the left	243 602		31	Stitch cam on the right short tuckE10-14+7.2	255 429
7	Support on the right	243 603			Stitch cam on the right short tuckE16-18+8.2	255 548
8	Support	239 295		32	Pressure part short tuck	255 430
11	Yarn control device	237 124		34	Raising cam plate	256 491
12	Yarn guide bracket complete	241 581		500	Self-locking screw M6x12	023 415
15	Friction feed wheel 16 fold on the left complete	244 991		501	Serrated nut M6-10	023 414
16	Friction feed wheel 16 fold on the right complete	244 992		502	Square nut M8	023 269
19	Deflector on the left complete	259 573		503	Pan-head screw M8x16	023 113
20	Deflector on the right complete	259 570		506	Dowel pin 6x16	020 677
21	Left clamping and cutting bed E10-14	253 682		507	Screw M6x20	244 824
	Left clamping and cutting bed E16-18 E8.2	253 684		508	Screw KB60x20	237 682
22	Clamping and cutting bed on the right E10-14	253 681		510	Pan-head screw M5x10	023 247

17.4 Overview of conversion kit with 32 IFF E10 | E12 | E14 | E16 | E18 | E8.2




17.5 Overview of conversion kit with 32 IFF E6.2

Pos	Designation	ID		Pos	Designation	ID
Σ	Conversion kit 32 IFF Type 2 E6.2	257 441		20	Deflector on the right complete	259 570
1	Magnetic holder complete	229 373		21	Left clamping and cutting bed E10-14	253 682
2	Additional bobbin board 50" IFF complete	244 424		22	Clamping and cutting bed on the right E10-14	253 681
3	Yarn tensioner on the left completeE7-8	244 499		25	DVD instructions conversion kit IFF	245 169
4	Yarn tensioner on the right complete E7-8	244 502		26	Adjusting part for yarn carrier bow	250 119
5	Yarn brake complete	244 347		27	Yarn guide complete IFF E7-8	245 162
6	Clamping bow	244 409		30	Stitch cam on the left short tuckE6.2	255 551
7	Ceramic eyelet	240 640		31	Stitch cam on the right short tuckE6.2	255 552
11	Yarn control device	237 124		32	Pressure part short tuck E6.2	255 430
12	Yarn guide bracket complete	241 581		34	Raising cam plate	256 491
15	Friction feed wheel 16 fold on the left complete	244 991		506	Dowel pin 6x16	020 677
16	Friction feed wheel 16 fold on the right complete	244 992		507	Screw M6x20	244 824
19	Deflector on the left complete	259 573		508	Screw KB60x20	237 682



17.6 Overview of conversion kit with 32 IFF
E7.2 | E6.2(12m.10) | E14/12


Pos	Designation	ID		Pos	Designation	ID
Σ	Conversion kit 32 IFF Type 2					
	E7.2 E6.2(12m.10) E14/12	256 990		22	Clamping and cutting bed on the right E10-14	253 681
1	Magnetic holder complete	229 373		24	Stopping device 16-fold complete	259 455
2	Additional bobbin board 50" IFF complete	244 424		25	DVD instructions conversion kit IFF	245 169
3	Yarn tensioner on the left completeE10-18	258 461		26	Adjusting part for yarn carrier bow	250 119
4	Yarn tensioner on the right complete E10-18	258 463		27	Yarn guide complete IFF E10-14	245 163
11	Yarn control device	237 124		28	Ceramic eyelet	240 640
12	Yarn guide bracket complete	241 581		30	Stitch cam on the left short tuckE10-14+7.2	255 428
15	Friction feed wheel 16 fold on the left complete	244 991		31	Stitch cam on the right short tuckE10-14+7.2	255 429
16	Friction feed wheel 16 fold on the right complete	244 992		32	Pressure part short tuck	255 430
17	Yarn deflector on the left complete	244 517		34	Raising cam plate	256 491
18	Yarn deflector on the right complete	244 521		506	Dowel pin 6x16	020 677
19	Deflector on the left complete	259 573		507	Screw M6x20	244 824
20	Deflector on the right complete	259 570		508	Screw KB60x20	237 682
21	Left clamping and cutting bed E10-14	253 682		510	Pan-head screw M5x10	023 247



17.7 Magnet holder


17.7 Magnet holder

Pos	Designation	ID		Pos	Designation	ID
Σ	Magnetic support complete	229 373				
1	Positioning pin	229 345		3	Felt circular blank 37mm	245 165
2	Flat gripper Pg40l	227 311		500	Countersunk head screw M5x16	023 417



17.8 Additional bobbin board


Pos	Designation		ID		Pos	Designation		ID
Σ	Additional bobbin board 50'' IFF complete		244 424					
1	Additional bobbin board welded		243 608		5	550	Dowel pin 3x12	020 647
2	Positioning pin		202 777			551	Eyelet	021 504
3	DiskD=130		062 385			552	Snap ring A12	020 996
4	Bobbin support		200 363		500	Pan-head screwM4x30		023 681
5	Yarn guide		243 765		501	Washer5,3x30x1,25		023 556
	5a	Guide part	243 623		502	Pan-head screwM4x25		023 511



17.9 Parts for the safety door on the left E10|E12|E14|E16|E18|E7.2|E8.2|E6.2(12m.10)|E14/12

17.9 Parts for the safety door on the left
E10|E12|E14|E16|E18|E7.2|E8.2|E6.2(12m.10)
|E14/12


Pos	Designation	ID		Pos	Designation	ID
3	Yarn tensioner on the left complete E10-18	258 461		28	Ceramic eyelet	240 640
19	Deflector on the left complete	259 573		508	Screw KB60x20	237 682



17.9 Parts for the safety door on the left E10|E12|E14|E16|E18|E7.2|E8.2|E6.2(12m.10)|E14/12

17.9.1 Yarn tensioner on the left
E10|E12|E14|E16|E18|E7.2|E8.2|E6.2(12m.10)|E14/12


Pos	Designation	Id	Pos	Designation	Id
Σ	Yarn tensioner on the left complete E10-18	258 461	7	Grounding plate of tension axle	243 121
1	Card yarn tensioner 16-fold on the left	241 345	8	Ground cable yarn tensioner OKC	243 105
2	Tension axle completeE10-18	258 460	500	Screw KB30x8	236 228
3	Housing	241 367	501	Circlip	021 022
4	Slider	241 694	502	Tension spring 4,9x0,45x53	023 504
5	Stop point	241 368	503	Circlip	021 020
6	Spacer	242 048	504	Countersunk screw M4x10	241 914



17.9 Parts for the safety door on the left E10|E12|E14|E16|E18|E7.2|E8.2|E6.2(12m.10)|E14/12


17.9.1.1 Tension axle E10|E12|E14|E16|E18|E7.2|E8.2|E6.2(12m.10)|E14/12

Pos	Designation	ID		Pos	Designation	ID
Σ	Tension axle complete E10-18	258 460		3	Thread clamp AKF	238 695
1	Axle	244 522		31	HousingAKF	238 689
2	Tension arm pre-assembled E10-18	258 459		32	Cover AKF	237 926
4	Wire bow	238 694		33	Sheet metal at the bottom (housing AKF)	240 719
500	Shim ring 8x14x0,5	023 501		34	Lever AKF	238 692
501	Circlip	021 022		35	Pressure piece AKF	238 690
502	Grooved pin 2x6	243 172		36	SliderAKF	238 691
				37	Wire bow	238 694
				38	Wire	237 940
				531	Screw KB 35x12	237 681
				532	Screw KB 40x8	236 227
				533	Compression spring0,30x4,50x18,50	241 437
				534	Grooved pin 2x6	243 172



17.9.2 Deflector on the left and on the right


Pos	Designation	ID		Pos	Designation	ID
ΣL	Deflector on the left complete	259 573		ΣR	Deflector on the right complete	259 570
1	Support of yarn deflector	257 286		1	Support of yarn deflector	257 286
2	Yarn deflector on the left	259 572		2	Yarn deflector on the right	259 569
500	Cap screwM4x16	023 123		500	Cap screwM4x16	023 123
501	Hexagon nut M4-8	023 046		501	Hexagon nut M4-8	023 046
502	Washer4	020 879		502	Washer4	020 879
900	Screw KB60x20	237 682		900	Screw KB60x20	237 682



17.10 Parts for the right safety door E10|E12|E14|E16|E18|E7.2|E8.2|E6.2(12m.10)|E14/12


17.10 Parts for the right safety door
E10|E12|E14|E16|E18|E7.2|E8.2|E6.2(12m.10)
|E14/12

Pos	Designation	ID		Pos	Designation	ID
4	Yarn tensioner on the right complete E10-18	258 463		28	Ceramic eyelet	240 640
20	Deflector complete	259 570		508	Screw KB60x20	237 682



17.10.1 Yarn tensioner on the right
E10|E12|E14|E16|E18|E7.2|E8.2|E6.2(12m.10)|E14/12


Pos	Designation	Id		Pos	Designation	Id
Σ	Yarn tensioner on the left complete E10-18	258 463		7	Grounding plate of tension axle	243 121
1	Card yarn tensioner 16-fold on the right	241 346		8	Ground cable yarn tensionerokc	243 105
2	Tension axle completeE10-18	258 460		500	Screw KB30x8	236 228
3	Housing	241 367		501	Circlip	021 022
4	Slider	241 694		502	Tension spring 4,9x0,45x53	023 504
5	Stop point	241 368		503	Circlip	021 020
6	Spacer	242 048		504	Countersunk screw M4x10	241 914



17.11 Parts for the safety door on the left E6.2


17.11 Parts for the safety door on the left E6.2

Pos	Designation	ID		Pos	Designation	ID
3	Yarn tensioner on the left completeE7-8	244 499		7	Ceramic eyelet	240 640
5	Yarn brake complete	244 347		19	Deflector on the left complete	259 573
6	Clamping bow	244 409		508	Screw KB60x20	237 682



17.11.1 Yarn tensioner on the left E6.2


Pos	Designation	Id		Pos	Designation	Id
Σ	Yarn tensioner on the left complete E7-8	244 499		7	Grounding plate of tension axle	243 121
1	Card yarn tensioner 16-fold on the left	241 345		8	Ground cable yarn tensionerokc	243 105
2	Tension axle completeE3-8	244 494		500	Screw KB30x8	236 228
3	Housing	241 367		501	Circlip	021 022
4	Slider	241 694		502	Tension spring 4,9x0,5x53	023 503
5	Stop point	241 368		503	Circlip	021 020
6	Spacer	242 048		504	Countersunk screw M4x10	241 914



17.11 Parts for the safety door on the left E6.2


17.11.1.1 Tension axle E6.2

Pos	Designation	ID	Pos	Designation	ID
Σ	Tension axle completeE6.2	244 494	3	Thread clamp AKF	238 695
1	Axle	244 522	31	HousingAKF	238 689
2	Tension arm pre-assembledE3-8	259 448	32	Cover AKF	237 926
4	Wire bow	238 694	33	Sheet metal at the bottom (housing AKF)	240 719
500	Shim ring 8x14x0,5	023 501	34	Lever AKF	238 692
501	Circlip	021 022	35	Pressure piece AKF	238 690
502	Grooved pin 2x6	243 172	36	SliderAKF	238 691
			37	Wire bow	238 694
			38	Wire	237 940
			531	Screw KB 35x12	237 681
			532	Screw KB 40x8	236 227
			533	Compression spring 0,30x4,50x18,50	241 437
			534	Grooved pin 2x6	243 172



17.11.2 Yarn brake


Pos	Designation	ID		Pos	Designation	ID
Σ	Yarn brake complete	244 347				
1	Support	240 607		4	Ceramic eyelet open	243 778
2	Slider	240 606		500	Compression spring 0,65x20,15x14,80	241 361
3	Brake disk	244 355		501	O-ring 11x2	241 434



17.12 Parts for the right safety door E6.2


17.12 Parts for the right safety door E6.2

Pos	Designation	ID		Pos	Designation	ID
4	Yarn tensioner on the right complete E7-8	244 502		7	Ceramic eyelet	240 640
5	Yarn brake complete	244 347		20	Deflector on the right complete	259 570
6	Clamping bow	244 409		508	Screw KB60x20	237 682



17.12.1 Yarn tensioner on the right E6.2


Pos	Designation	Id		Pos	Designation	Id
Σ	Yarn tensioner on the right complete E7-8	244 502		7	Grounding plate of tension axle	243 121
1	Card yarn tensioner 16-fold on the right	241 346		8	Ground cable yarn tensionerokc	243 105
2	Tension axle completeE7-8	244 494		500	Screw KB30x8	236 228
3	Housing	241 367		501	Circlip	021 022
4	Slider	241 694		502	Tension spring 4,9x0,5x53	023 503
5	Stop point	241 368		503	Circlip	021 020
6	Spacer	242 048		504	Countersunk screw M4x10	241 914



17.13 Parts for the yarn guide system with 18 FKE


17.13 Parts for the yarn guide system with 18 FKE

Pos	Designation	ID		Pos	Designation	ID
Σ	Parts of the yarn guide system with 18 FKE E10 E12 E14 E16 E18 E8.2					
5	Yarn guide bar	240 324		12	Yarn guide bracket complete	241 581
6	Support on the left	243 602		500	Self-locking screw M6x12	023 415
7	Support on the right	243 603		501	Serrated nut M6-10	023 414
8	Support	239 295		502	Square nut M8	023 269
11	Yarn control device	237 124		503	Pan-head screwM8x16	023 113



17.14 Parts for the yarn guide system with 12 and 14 FKE


Pos	Designation	ID		Pos	Designation	ID
Σ	Parts of the yarn guide system with 12 and 14 FKE					
11	Yarn control device	237 124		12	Yarn guide bracket complete	241 581



17.15 Friction feed wheel on the left and on the right complete

17.15 Friction feed wheel on the left and on the right complete


Pos	Designation	ID		Pos	Designation	ID
ΣL	Friction feed wheel 16 fold on the left complete	244 991		ΣR	Friction feed wheel 16 fold on the right complete	244 992
1	Friction feed wheel on the left	244 185		1	Friction feed wheel on the right	244 186
2	Support on the left	243 869		2	Support right	244 142
501	Pan-head screwM8x25	023 027		501	Pan-head screwM8x25	023 027
502	Cap screwM6x16	020 135		502	Cap screwM6x30	020 138
503	Pan-head screwM5x8	239 408		503	Pan-head screwM5x8	239 408



17.15 Friction feed wheel on the left and on the right complete

17.15.1 Friction feed wheel on the left


Pos	Designation		ID		Pos	Designation	ID
Σ	Friction feed wheel 16 fold on the left complete		244 185		10	Cover	251 098
1	Housing		240 368		11	Bush	221 391
2	Friction roller complete		243 860		12	V-ribbed belt pulley	221 268
3	Three-phase AC motor 3x42V complete		219 800		13	Ribbed V-belt	206 927
	3a	Three-phase AC motor	220 161		14	Rod	243 868
	3b	Microswitch	008 664		15	Cover	230 758
5	Yarn guide rod 16-fold complete		244 576		18	Deflector complete 16-fold	250 102
6	Yarn guide rod 16-fold complete		244 578		20	Grounding plate	256 622
	6a	Yarn guide rod 16-fold	244 577		21	Spring plate	256 702
	6b	Ceramic eyelet	240 640		500	Screw KB30x8	236 228
7	Stop motion rail on the right complete		243 863		501	Screw M20x10	244 736
	7a	Stop motion rail on the right	243 864		502	Cap screwM5x12	020 132
	570	Slide bearing GFM-101214-07	023 627		503	Cap screwM5x16	022 726
	571	Guide piece	259 453		504	Cap screwM5x25	023 523
8	Stop motion rail on the left complete		243 865		506	Washer5,3x22x2,5	023 219
	8a	Stop motion rail on the left	243 866		507	Washer5	020 901
	8b	Eyelet	230 662		508	Shim ring 15x21x1	023 216
	580	Slide bearing GFM-101214-07	023 627		510	Washer5	023 542
	581	Guide piece	259 453		511	Pan-head screwM5x8	239 408
9	Bracket		251 113		514	Pan-head screwM4x8	023 579



17.15 Friction feed wheel on the left and on the right complete


17.15.2 Friction feed wheel on the right

Pos	Designation	ID	Pos	Designation	ID
Σ	Friction feed wheel 16 fold on the right complete	244 186	10	Cover	251 098
1	Housing	240 368	11	Bush	221 391
2	Friction roller complete	243 860	12	V-ribbed belt pulley	221 268
3	Three-phase AC motor 3x42V complete	219 800	13	Ribbed V-belt	206 927
	3a Three-phase AC motor	220 161	14	Rod	243 868
	3b Microswitch	008 664	15	Cover	230 758
5	Yarn guide rod 16-fold complete	244 772	18	Deflector complete 16-fold	250 102
6	Yarn guide rod 16-fold complete	244 578	20	Grounding plate	256 622
	6a Yarn guide rod 16-fold	244 577	21	Spring plate	256 702
	6b Ceramic eyelet	240 640	500	Screw KB30x8	236 228
7	Stop motion rail on the right complete	243 863	501	Screw M20x10	244 736
	7a Stop motion rail on the right	243 864	502	Cap screwM5x12	020 132
	570 Slide bearing GFM-101214-07	023 627	503	Cap screwM5x16	022 726
	571 Guide piece	259 453	504	Cap screwM5x25	023 523
8	Stop motion rail on the right complete	244 530	506	Washer5,3x22x2,5	023 219
	8a Stop motion rail on the right	244 531	507	Washer5	020 901
	8b Eyelet	230 662	508	Shim ring 15x21x1	023 216
	580 Slide bearing GFM-101214-07	023 627	510	Washer5	023 542
	581 Guide piece	259 453	511	Pan-head screwM5x8	239 408
9	Bracket	251 113	514	Pan-head screwM4x8	023 579



17.16 Left clamping and cutting bed E10|E12|E14|E6.2|E7.2|E6.2(E12m.10)|E14/12


Pos	Designation	Id	Pos	Designation	Id
Σ	Left clamping and cutting bed E10-14	253 682	11	Tuck needle on the left E5-14	244 630
1	Guide plate EPT on the left E5-14	257 236	12	Intermediate cam E10-14	244 591
1a	Guide plate on the left E10-14	257 232	13	Coupling part E5-8	253 381
1b	Cover rail	243 923	14	Intermediate slider with brake E5-8	255 534
1c	Cover rail	243 924	15	Selection jack E4-8	200 687
1d	Locating wire	243 925	16	Selector spring E4-8	200 690
1e	Axle	257 201	17	Holding strip on the left	256 996
1f	Guide pin	211 351	18	Deflector plate on the left	255 556
1g	Locating wire	215 927	19	Spring holder	255 724
1h	Locating wire	244 589	20	Threaded bolt	255 723
510	Dowel pin 3x14	252 771	500	Cap screw M4x10	023 136
511	Setscrew M5x5	236 061	501	Hexagon nut M4	023 046
2	Cover on the left complete E10-14	251 120	502	Washer 4	020 870
3	Catch hook on the left E10-18	255 622	503	Pan-head screw M3x10	242 029
4	Slider E10-14	253 089	504	Tension spring 5x0,5x17,4	023 377
5	Intermediate cam E10-14	253 090	505	Compression spring 07x4,3x12,1	023 521
6	Blade	243 948	507	Springy thrust piece	023 403
7	Clamp on the left complete	244 633	570*	Cap screw M6x20	244 824



17.17 Left clamping and cutting bed E16|E18|E8.2


17.17 Left clamping and cutting bed E16|E18|E8.2

Pos	Designation		Id	Pos	Designation		Id
Σ	Left clamping and cutting bed E16-18		253 684	11	Tuck needle on the left E16-18		244 740
1	Guide plate EPT on the left E16-18		257 238	12	Intermediate cam		244 741
	1a	Guide plate on the left E16-18	257 234	13	Coupling part E10-12		253 382
	1b	Cover rail	243 923	14	Intermediate slider with brake E10-12		255 535
	1c	Cover rail	243 924	15	Selection jack E10-12		200 688
	1d	Locating wire	243 925	16	Selector spring E10-12		200 691
	1e	Axle	257 201	17	Holding strip on the left		256 996
	1f	Guide pin	211 351	18	Deflector plate on the left		255 556
	1g	Locating wire	215 927	19	Spring holder		255 724
	1h	Locating wire	244 589	20	Threaded bolt		255 723
	510	Dowel pin 3x14	252 771	500	Cap screw M4x10		023 136
	511	Setscrew M5x5	236 061	501	Hexagon nut M4		023 046
2	Cover on the left complete E16-18		242 835	502	Washer4		020 870
3	Catch hook on the left E10-18		255 622	503	Pan-head screw M3x10		242 029
4	SliderE16-18		253 095	504	Tension spring 5x0,5x17,4		023 377
5	Intermediate cam E16-18		253 096	505	Compression spring 07x4,3x12,1		023 521
6	Blade		243 948	507	Springy thrust piece		023 403
7	Clamp on the left complete		244 633	570*	Cap screw M6x20		244 824



17.18 Right clamping and cutting bed E10|E12|E14|E6.2|E7.2|E6.2(E12m.10)|E14/12


Pos	Designation	Id	Pos	Designation	Id
Σ	Clamping and cutting bed on the right E10-14	253 681	11	Tuck needle on the right E10-14	244 592
1	Guide plate EPT on the right E5-14	257 235	12	Intermediate cam E10-14	244 591
1a	Guide plate on the right E5-14	257 231	13	Coupling part E5-8	253 381
1b	Cover rail	243 923	14	Intermediate slider with brake E5-8	255 534
1c	Cover rail	243 924	15	Selection jack E4-8	200 687
1d	Locating wire	243 925	16	Selector spring E4-8	200 690
1e	Axle	257 201	17	Holding strip on the right	256 995
1f	Guide pin	211 351	18	Deflector plate on the right	255 555
1g	Locating wire	215 927	19	Spring holder	255 724
1h	Locating wire	244 589	20	Threaded bolt	255 723
510	Dowel pin 3x14	252 771	500	Cap screw M4x10	023 136
511	Setscrew M5x5	236 061	501	Hexagon nut M4	023 046
2	Cover on the right complete E10-14	251 119	502	Washer 4	020 870
3	Catch hook on the right complete E10-18	255 620	503	Pan-head screw M3x10	242 029
4	Slider E10-14	253 089	504	Tension spring 5x0,5x17,4	023 377
5	Intermediate cam E10-14	253 090	505	Compression spring 07x4,3x12,1	023 521
6	Blade	243 948	507	Springy thrust piece	023 403
7	Clamp on the right complete	244 602	570*	Cap screw M6x20	244 824



17.19 Right clamping and cutting bed E16|E18|E8.2


17.19 Right clamping and cutting bed E16|E18|E8.2

Pos	Designation		Id	Pos	Designation		Id
Σ	Clamping and cutting bed on the right E16-18		253 683	11	Tuck needle on the right E16-18		244 739
1	Guide plate EPT on the right E3		257 237	12	Intermediate cam		244 741
	1a	Guide plate on the rightE3	257 233	13	Coupling part E10-12		253 382
	1b	Cover rail	243 923	14	Intermediate slider with brake E10-12		255 535
	1c	Cover rail	243 924	15	Selection jack E10-12		200 688
	1d	Locating wire	243 925	16	Selector spring E10-12		200 691
	1e	Axle	257 201	17	Holding strip on the right		256 995
	1f	Guide pin	211 351	18	Deflector plate on the right		255 555
	1g	Locating wire	215 927	19	Spring holder		255 724
	1h	Locating wire	244 589	20	Threaded bolt		255 723
	510	Dowel pin 3x14	252 771	500	Cap screwM4x10		023 136
	511	Setscrew M5x5	236 061	501	Hexagon nut M4		023 046
2	Cover on the right complete E16-18		242 836	502	Washer4		020 870
3	Catch hook on the right complete E10-18		255 620	503	Pan-head screw M3x10		242 029
4	SliderE16-18		253 095	504	Tension spring 5x0,5x17,4		023 377
5	Intermediate cam E16-18		253 096	505	Compression spring 07x4,3x12,1		023 521
6	Blade		243 948	507	Springy thrust piece		023 403
7	Clamp on the right complete		244 602	570*	Cap screwM6x20		244 824



17.20 Stopping device


Pos	Designation	ID		Pos	Designation	ID
L+R	Stopping device 16-fold complete	259 455		2	Yarn brake	259 440
1	Support plate	259 401		510	Pan-head screwM5x10	023 247



17.21 Yarn guide complete (24 IFF) E10|E12|E14|E7.2|E6.2(12m.10)|E14/12


17.21 Yarn guide complete (24 IFF)
E10|E12|E14|E7.2|E6.2(12m.10)|E14/12

Pos	Designation	Id	Pos	Designation	Id
Σ	Yarn guide complete E10-14 IFF 24	256 936			
1	IFF carriage complete 1+8 E10-14 (6 pieces)	259 740	5	Limiter on the left with two eyelets (6 pieces)	244 446
	1a IFF carriage 1+8	259 728		550 Eyelet holder complete	022 324
	1b Yarn carrier head 1+8 complete E10-14	250 008		551 Eyelet holder complete	022 323
2	IFF carriage complete 2+7 E10-14 (6 pieces)	259 741		552 Eyelet 4,2	021 499
	2a IFF carriage 2+7	259 729		553 Cap screwM3,5x4	020 011
	2b Yarn carrier head 2+7 complete E10-14	250 009	6	Limiter on the right with two eyelets (6 pieces)	244 445
3	IFF carriage complete 3+6 E10-14 (6 pieces)	259 742	c	Yarn guide angle	242 863
	3a IFF carriage 3+6	259 730	500	Pan-head screw M4x5	239 549
	3b Yarn carrier head 3-6 complete E10-14	250 010	501	Washer4	020 870
4	IFF carriage complete 4+5 E10-14 (6 pieces)	259 743			
	4a IFF carriage 4+5	259 731			
	4b Yarn carrier head 3-6 complete E10-14	250 010			




17.22 Yarn guide complete (24 IFF) E16 | E18 | E8.2

Pos	Designation	Id	Pos	Designation	Id
Σ	Yarn guide complete E16-18 IFF 24	256 937			
1	IFF carriage complete 1+8 E16-18 (6 pieces)	259 744	5	Limiter on the left with two eyelets (6 pieces)	244 446
	1a IFF carriage 1+8	259 728		550 Eyelet holder complete	022 324
	1b Yarn carrier head 1+8 complete E16-18	250 011		551 Eyelet holder complete	022 323
2	IFF carriage complete 2+7 E16-18 (6 pieces)	259 745		552 Eyelet 4,2	021 499
	2a IFF carriage 2+7	259 729		553 Cap screwM3,5x4	020 011
	2b Yarn carrier head 2+7 complete E16-18	250 012	6	Limiter on the right with two eyelets (6 pieces)	244 445
3	IFF carriage complete 3+6 E16-18 (6 pieces)	259 746	c	Yarn guide angle	242 863
	3a IFF carriage 3+6	259 730	500	Pan-head screw M4x5	239 549
	3b Yarn carrier head 3-6 complete E16-18	250 013	501	Washer4	020 870
4	IFF carriage complete 4+5 E16-18 (6 pieces)	259 747			
	4a IFF carriage 4+5	259 731			
	4b Yarn carrier head 3-6 complete E16-18	250 013			




17.23 Yarn guide complete (24 IFF) E6.2

Pos	Designation	Id	Pos	Designation	Id
Σ	Yarn guide complete E7-8 IFF 24	256 935			
1	IFF carriage complete 1+8 E7-8 (6 pieces)	259 736	5	Limiter on the left with two eyelets (6 pieces)	244 446
	1a IFF carriage 1+8	259 728		550 Eyelet holder complete	022 324
	1b Yarn carrier head 1+8 complete E7-8	244 082		551 Eyelet holder complete	022 323
2	IFF carriage complete 2+7 E7-8 (6 pieces)	259 737		552 Eyelet 4,2	021 499
	2a IFF carriage 2+7	259 729		553 Cap screwM3,5x4	020 011
	2b Yarn carrier head 2+7 complete E7-8	244 083	6	Limiter on the right with two eyelets (6 pieces)	244 445
3	IFF carriage complete 3+6 E7-8 (6 pieces)	259 738	c	Yarn guide angle	242 863
	3a IFF carriage 3+6	259 730	500	Pan-head screw M4x5	239 549
	3b Yarn carrier head 3-6 complete E7-8	244 084	501	Washer4	020 870
4	IFF carriage complete 4+5 E7-8 (6 pieces)	259 739			
	4a IFF carriage 4+5	259 731			
	4b Yarn carrier head 3-6 complete E7-8	244 084			




17.24 Yarn guide complete (32 IFF)
E10|E12|E14|E7.2|E6.2(12m.10)|E14/12

Pos	Designation	Id	Pos	Designation	Id
Σ	Yarn guide complete E10-14 IFF	245 163			
1	IFF carriage complete 1+8 E10-14 (8 pieces)	259 740	5	Limiter on the left with two eyelets (8 pieces)	244 446
	1a IFF carriage 1+8	259 728		550 Eyelet holder complete	022 324
	1b Yarn carrier head 1+8 complete E10-14	250 008		551 Eyelet holder complete	022 323
2	IFF carriage complete 2+7 E10-14 (8 pieces)	259 741		552 Eyelet 4,2	021 499
	2a IFF carriage 2+7	259 729		553 Cap screw M3,5x4	020 011
	2b Yarn carrier head 2+7 complete E10-14	250 009	6	Limiter on the right with two eyelets (8 pieces)	244 445
3	IFF carriage complete 3+6 E10-14 (8 pieces)	259 742	c	Yarn guide angle	242 863
	3a IFF carriage 3+6	259 730	500	Pan-head screw M4x5	239 549
	3b Yarn carrier head 3-6 complete E10-14	250 010	501	Washer4	020 870
4	IFF carriage complete 4+5 E10-14 (8 pieces)	259 743			
	4a IFF carriage E10-14	259 731			
	4b Yarn carrier head 3-6 complete E10-14	250 010			



17.25 Yarn guide complete (32 IFF) E16|E18|E8.2

Pos	Designation	Id	Pos	Designation	Id
Σ	Yarn guide complete E16-18 IFF	245 164			
1	IFF carriage complete 1+8 E16-18 (8 pieces)	259 744	5	Limiter on the left with two eyelets (8 pieces)	244 446
	1a IFF carriage 1+8	259 728		550 Eyelet holder complete	022 324
	1b Yarn carrier head 1+8 complete E16-18	250 011		551 Eyelet holder complete	022 323
2	IFF carriage complete 2+7 E16-18 (8 pieces)	259 745		552 Eyelet 4,2	021 499
	2a IFF carriage 2+7	259 729		553 Cap screwM3,5x4	020 011
	2b Yarn carrier head 2+7 complete E16-18	250 012	6	Limiter on the right with two eyelets (8 pieces)	244 445
3	IFF carriage complete 3+6 E16-18 (8 pieces)	259 746	c	Yarn guide angle	242 863
	3a IFF carriage 3+6	259 730	500	Pan-head screw M4x5	239 549
	3b Yarn carrier head 3-6 complete E16-18	250 013	501	Washer4	020 870
4	IFF carriage complete 4+5 E16-18 (8 pieces)	259 747			
	4a IFF carriage 4+5	259 731			
	4b Yarn carrier head 3-6 complete E16-18	250 013			



17.26 Yarn guide complete (32 IFF) E6.2

Pos	Designation		Id	Pos	Designation		Id	
Σ	Yarn guide complete E7-8 IFF		245 162					
1	IFF carriage complete 1+8 E7-8 (8 pieces)		259 736		5	Limiter on the left with two eyelets (8 pieces)		244 446
	1a	IFF carriage 1+8	259 728			550	Eyelet holder complete	022 324
	1b	Yarn carrier head 1+8 complete E7-8	244 082			551	Eyelet holder complete	022 323
2	IFF carriage complete 2+7 E7-8 (8 pieces)		259 737			552	Eyelet 4,2	021 499
	2a	IFF carriage 2+7	259 729			553	Cap screwM3,5x4	020 011
	2b	Yarn carrier head 2+7 complete E7-8	244 083		6	Limiter on the right with two eyelets (8 pieces)		244 445
3	IFF carriage complete 3+6 E7-8 (8 pieces)		259 738		c	Yarn guide angle		242 863
	3a	IFF carriage 3+6	259 730		500	Pan-head screw M4x5		239 549
	3b	Yarn carrier head 3-6 complete E7-8	244 084		501	Washer4		020 870
4	IFF carriage complete 4+5 E7-8 (8 pieces)		259 739					
	4a	IFF carriage 4+5	259 731					
	4b	Yarn carrier head 3-6 complete E7-8	244 084					

